



# W.H. BRESHEARS, INC.

PETROLEUM MARKETING & DISTRIBUTION  
MOTOR FUELS • LUBRICANTS • ALTERNATIVE FUELS

720 B Street, Modesto, CA 95354  
1-800-637-4427 • (209) 522-7291



## W.H. Breshears, Inc. Automatic Transmission Fluid DEXRON III / MERCON

### Description:

- W.H. Breshears, Inc. MP ATF is a high-performance multi-purpose power transmission fluid that is specially formulated for systems requiring DEXRON®-III and MERCON® finished oils.
- W.H. Breshears, Inc. MP ATF is manufactured using highly re-refined paraffinic base oils and a select additive package with an extremely shear stable V.I. improver.
- W.H. Breshears, Inc. MP ATF provides superior thermal and oxidative stability, and corrosion and wear protection that will prevent the formation and accumulation of deposits and sludge.

### Typical Applications:

- W.H. Breshears, Inc. MP ATF is acceptable for use in passenger cars and light-duty trucks where the manufacturer recommends a DEXRON® or MERCON® fluid.

### Physical Properties:

|                         |         |
|-------------------------|---------|
| API Gravity             | 33.1    |
| Color, ASTM D-1500      | 2.5 max |
| Viscosity @ 40°C, cSt   | 34.15   |
| Viscosity, @ 100°C, cSt | 7.4     |
| Viscosity Index         | 191     |
| Flash Point (PMCC), °C  | >170    |
| Pour Point, °C          | -18     |
| Appearance              | Red     |

### Storage and Handling:

Maximum temperatures of 60°C (140°F) for handling and 38°C (100°F) for long-term storage are recommended. Typical precautions for handling concentrated chemicals and blending additives into base oils and solvents should be observed.

*Quality in Every Gallon Sold*