

GASWARDEN SENSOR

Flammable / Toxic / Oxygen / Refrigerant - Gas Alarm

- Sensors pre-set and tested
- Sensor types:
toxic/flammable/oxygen/
refrigerant/carbon dioxide
- Three pre-set alarm levels
(timed ON/OFF option)
- Audible visual alarms & relays
- Designed for ease of installation
- AC mains version



Sensors for use in commercial and light industrial applications, such as laboratories, workshops, hotels, offices, boiler plant rooms, etc. are available for monitoring toxic, flammable, oxygen or refrigerant gases. The gas sensor continuously monitors the atmosphere for hazardous conditions. On detection of gas the sensor will indicate the gas level status A1, A2, A3 by LED indication and sounder. Further actions can be initiated by the alarm relays.










For multi sensor systems the GASWARDEN 4 zone alarm panel (part No, 204-000) data sheet C1667 may be used to provide centralised alarm functions.

Specification

Not for use in hazardous zone areas

Sensor Type	Flammable - catalytic Toxic, Oxygen - electrochemical Refrigerant - semiconductor CO2 - infrared
Power Supply	18 to 30vDC optional 90-260vAC
Consumption	1.2 W
Alarm Relays	Signal Relay: 1 SPCO volt free contact 3A @ 230vAC Global A1/A2/A3 A2/A3 only option latched/unlatched - selectable N/E - N/D Mains Relay: (mains option only) Permanent mains N/E - N/C Off/on alarm (solenoid valve control)
Indicators	Power (Green LED) Gas alarm - Green LED to Red A1 - slow flash + intermittent sounder A2 - rapid flash + high rate sounder A3 - constant + constant sounder Fault - Amber + constant sounder
Sounder	85dB @ 10cm Permanent mute option
Ambient Temp	Operation: -5 to +50°C Storage: +5 to +55°C
Protection	Standard Sensor - IP42 Weatherproof - IP64
Dimensions	Standard L 83mm x H 83mm x D 36mm Weatherproof L 145mm x H 145mm x D 60mm
Options	Duct sensor probe - L27mm x 28mm diameter

Options

	24vDC surface or dry lining box mount
	Mains - surface or dry lining box mount
	Surface mount with duct probe
	Surface mount sensor - weatherproof
	Duct mount (probe) - weatherproof
	Interface unit - various inputs see C1690
	Remote Sensor (flammable gases)
	Sensor stand alone power supply
	Gaswarden 4 zone alarm panel

