Natural Daylight Solutions Ltd

NDS Ultra Dome

The NDS Ultra Dome is architecturally inspired to deliver maximum security with an aluminium frame creating a contemporary fnish.

These units have tamper-proof fixings concealed under the aluminium frame. With a secret lock system which can only be opened with the Ultra security key.

The aluminium frame is supplied as standard in a silver anodised finish, Powder coated to a Standard RAL colour is an optional extra cost.

Glazed with a low rise dome or pyramid shaped polycarbonate.

Options available:

Glazing: Clear, Textured, Opal or Bronze

Configuration: Fixed unit, Manual /Solar or Electric opening.

Kerb: Standard Height PVC kerb - Tall PVC kerb - Builders kerb attachment

Optional Kerb ACC: Kerb adapter for non-standard sizes

U. Value: 1.25—1.8 Ug-Value (Wm2k)


Light Transmission: 30—78% (%) DIN 5036

Acoustics: Available for fixed units only achieving a reduction of 15dB for every 10dB present

Ventilation: Trickle, Automatic humidity, Mechanical vents

Automation: Remote, Sensor controlled, solar powered or wireless sensor

Accessories: Security grille, Blinds & Manual opening pole



Suite 20, Fairfield Enterprise Centre
Lincoln Way
Fairfield Industrial Estate
Louth
Lincolnshire
LN11 0LS
T: 0333 772 0609
M: 07834 010311

