



SUBMITTAL DATA  
SHEET METAL FITTINGS

**STRAIGHT COLLARS**

**Straight Spin Fittings**

( Tolerance on all sizes +/- 1/8")

Nom. Dia.	O.D.	Length No Damper Standard Damper	Length With Build Out	Cut Hole Size
4"	3.875	5"	7"	3.75
6"	5.875	5"	7"	5.75
8"	7.875	5"	7"	7.75
10"	9.875	5"	7"	9.75
12"	11.875	5"	7"	11.75
14"	13.875	5"	7"	13.75
16"	15.875	5"	7"	15.75
18"	17.875	5"	7"	17.75
20"	19.875	5"	7"	19.75

**Fitting Model**

- SOC No Damper
- SOCD Standard Damper – Spring End Bearing with Handle and Wingnut
- SOCD1 2" Damper Handle Extension
- SOCD3 2" Build Out – 3/8 " square shaft, Nylon End Bearings and Locking Handle

**Standard Construction**

- G90 Galvanized Steel, 26 Ga. thru 12" Dia., 24 Ga. on 14" Dia. and above

**Gauge Options**

- 24 Gauge
- 22 Gauge
- 20 Gauge
- Other \_\_\_\_\_

**Material Options**

- Galvanized Steel
- Aluminum
- Stainless Steel
- Other \_\_\_\_\_