

# Lighting Your Way

**LURA LINE**  
LIGHTING

## OmniLED A-Lamps

Unlike traditional LED lighting, the OmniLED A-Lamp from Luraline allows the light to go in a 230 degree pattern. This makes our Omni-Directional LEDs ideal anywhere incandescent light sources are traditionally used. These 120-volt, 10 watt lamps generate 825 lumens of light output while providing a savings of up to 85% over halogen alternatives. The OmniLED lamps feature instant-on capabilities and are dimmable from 100% down to 5%. Rated for outdoor use when protected from the elements, these lamps perform well in humidity both indoors and out.

This lamp is available with a choice of bases - standard medium base (E26) or bi-pin base (GU24). Seamlessly transition almost any fixture to LED with the OmniLED A-Lamps.

### Features

- Instant-on
- Omni-directional 230° beam spread
- Dimming from 100% to 5%.
- Up to 85% energy savings compared to halogen alternatives
- Long life - 25,000 hours significantly reduces lamp replacement costs
- Excellent CCT consistency and high color rendering (CRI)
- Rated for use in enclosed fixtures
- UL listed - suitable for damp locations
- Withstands humidity indoors and outdoors

Specifications	E26 Base	GU24 Base
Ordering Code	L10A19	L10A19GU
Wattage (W)	10	10
Incandescent Equivalent (W)	60	60
Input Voltage (VAC)	120	120
Lumen Output (lm)	825	825
Color Temperature (CCT)	3000K	3000K
L70 Lifetime (Hours)	25000	25000
Length (MOL)	4.5"	4.3"
Diameter	2.6"	2.4"
Socket Base	E26	GU24
CRI	82	82
Dimming	Triac*	Triac*
Beam Spread (Degrees)	230	230
Warranty (Years)	3	3

\* Not compatible with ELV type dimmers



E26 Base



GU24 Base

