



SMPM 500hm Connectors

DC to 65GHz
Precision Series

Optimized Performance
Ruggedized Material Construction
30% Smaller than SMP
Low VSWR & Insertion Loss
Op. Temp -65C to 165C
Full Detent PCB for Positive Lock



| Description | ConductRF # | Frequency |
|--|---------------|-------------|
| SMPM with Female Contacts - Direct Solder | | |
| FOR RG-405 CABLE | PMF11A-A28G01 | DC to 65GHz |
| FOR RG-405 CABLE | PMF12A-A28G01 | DC to 65GHz |
| BULKHEAD, FOR RG-405 | PMF31A-A28G01 | DC to 65GHz |
| BULKHEAD, TEMP-FLEX 047SC-2901 | PMF31B-A33G01 | DC to 40GHz |
| MITER RT. ANGLE, FOR TEMP-FLEX 047SC-2901 | PMF21B-A33G01 | DC to 20GHz |
| RT. ANGLE FOR 0.047" CABLE | PMF21A-A33G01 | DC to 20GHz |
| SMPM with Male Contacts - Full Detent | | |
| PCB SURFACE MOUNT (.264 HIGH) | PMM11A-SPCG01 | DC to 65GHz |
| PCB SURFACE MOUNT (.140 HIGH) | PMM12A-SPCG01 | DC to 65GHz |
| Between Series Adapters to 2.92mm | | |
| ADAPTER, SMPM FEMALE TO 2.92mm JACK | BA-PDF-PMF-50 | DC to 40GHz |
| ADAPTER, SMPM MALE to 2.92mm JACK | BA-PDF-PMM-50 | DC to 40GHz |

Images for illustration only, Data subject to change.

