

- UCC-2HD10BT-U32

KEY FEATURES



- Resolution: Up to 1080P,720P
- Zoom: Optical 10X
- HAV: 63 degree
- Video Output: USB3.0, USB2.0 Compatible
- Independent HDMI and USB video outputs
- Extension module: HDMI output (Optional)
- Supports UVC1.5, UAC2.0
- Power: DC 12V
- Use with Familiar UC Software Video Applications

DESIGN



- Compact and contemporary design, use for Huddle Space and Mid-Size or smaller conference room.
- Independent HDMI and USB video outputs.
- Use with popular UC Video Applications. Works with popular cloud based video conferencing software or APPs.
- Camera is integrated with quiet pan and tilt Stepper Motor to ensure accuracy, smoothness and speed in control.
- Extension Module Provides HDMI video output and audio input and RS232/422/485 control.

FUNCTIONALITY

- Ideal for Huddle Space to Mid-Size video-conferencing, video communication Plug-N-Play.
- Built-in Mic, External audio input (Optional).
- ± 350 degrees continuous pan, ± 120 degrees continuous tilt
- 128 presets, 6 Preset speed adjustable up to 260 degrees/s
- Control: IR Remote Controller.
- Optional: RS232, RS422/485.
- Standard mounting and ceiling mounting with E-Flip function
- Extension Module (Optional)provides: HDMI Video output, Audio input, RS232, RS422/485 control.



UCC-2HD10B-U32



UCC-EXT-U3 (Optional)

Product Specification

Model No.	UCC-2HD10BT-U32
Camera	10X-BT
Image Sensor	1/2.86" CMOS 2.2MP
Lens	6.53~62.18mm
Digital Zoom	12X
Horizontal Angle of View	48°(W)~4.9°(T)
Aperture	F1.8(W)~F2.5(T)
Min. Illumination	0.2 lux(F1.8,IRC Close), 0.005 lux(F1.8, IRC Open)
Shutter Speed	1/1~1/10000s
Focus	Auto,Push.Manual
White Balance	Auto, Manual
Exposure	Auto,Manual,Shutter/Iris Priority Mode
Day/Night/Auto ICR	YES
Backlight Compensation	YES
WDR	YES
Privacy Zone Masking	-
Noise Reduction	2D/3D
S/N Ratio	≥50db
Image Stabilization	-
Image Flipper	YES
OSD	YES
Mechanical	
Pan Movement	Horizontal:±350 degrees continuous pan (Zoom Adaptive Speed Range: 0.05°~100°/S)
Tilt Movement	Vertical:+90 degrees to -30 degrees (Zoom Adaptive Speed Range: 0.05°~72°/S)
Preset Position	128 (Speed adjustable: Up to 200°/S, 6 presets on remote controller.)
Preset Speed	0~5 Level Adjustable
Home Position	Support
Environmental	Indoor
Interface	
Video Output	USB3.0, USB2.0 Compatible
Video Extension Module(Optional)	HDMI 1.4, CVBS(Inactive)
Video Format (HDMI)	HDMI: 1080p:60/50/30/25; 720p:60/50
Video Format (USB3.0/2.0)	1920x1080 1280x720 1024x768 960x540 850x480 800x600 768x448 720x576 20x540 720x480 720x404 640x480 640x360 352x288
Audio I/O	Built-in Mic, Audio input x1, 3.5mm audio jack (Optional)
Control Interface	IR Remote Controller, UVC1.5
Control Extension Module	RS232/RS422/RS485 (Optional)
Control Protocol	VISCA, PELCO P/D
Compatible Integration	USB3.0, UVC1.5 & UAC2.0
General	
Operating Temperature	-10 to +50 (°C)
Operating Humidity	≤80% Suitable for Use
Power Input	DC12V
Power Consumption	12W
Dimension	145x154mm
Weight	0.9kg

ORDER INFORMATION

- UCC-2HD10BT-U32B (Color Black)
- UCC-2HD10BT-U32W (Color White)
- UCC-2EXM-H (Extension Module, order separately)