

CPS SERIES: COLD WATER, GAS ENGINE







EK



COLD PRESSURE WASHER GAS POWERED

Long Life:

Built with the same chassis design & components as our proven hot water wash skids.

Rugged "Pro-tect-it" Frame:

Hydro Tek's unique "Pro-tect-it" frame of heavy gauge steel, with durable electrostatically applied powder coat finish give greater protection to engine and other vital components. Heavy duty 1¼" structural tubing frame, with built-in lifting bars, offers flexible mounting options: trailer, tank skid, stationary, or add a wheel kit for a portable washer.

Industrial Engines:

Smooth running twin cylinder gas engine. Overhead valve, pressure lubrication, and oil filtration along with reserve horsepower delivers 50% longer life than single cylinder powered washers. Electric start, low oil shutdown engine starts with the turn of a key and shuts off automatically if oil pressure drops. GX390 Honda is a single cylinder

Panel Mounted Unloader:

The unloader is frame mounted eliminating heat failures and vibration and is a pressure activated unloader for consistent and dependable operation.

Belt Drive Pump:

Low RPM drive pump runs cooler and quieter for continuous performance. These industrial triplex, ceramic plunger pumps outperform the competition in longevity.

EZ Align™ Belt System:

Tensioning system allows for easy belt adjustment with a single adjustment bolt. If you need to remove the pump for preventative maintenance, it is as simple as removing bolts, no need to reach underneath the washer.

Remote Fuel Tanks*:

Gas engine models have a 4 gallon fuel tank which is located away from the engine reducing risk of fire from gas spills. Extra capacity tank extends running time up to three times longer. *GX390 Honda has a 6.4qt integrated gas tank

More standard features:

- Nozzles with insulated quick couplers (twist on for CPS50005)
- Heavy-duty, 50' high pressure hose
- Heavy duty, insulated wand with trigger gun
- Twist coupler hose connection to easily remove gun/wand for storage or to add additional lengths of hose







Specifications				
Model	PSI	GPM	CC	Engine
CPS30005HH	3000	4.7	389	GX390 Honda Gas
CPS30005VH	3000	5.2	479	Vanguard Gas
CPS30008VG	3000	7.5	627	Vanguard Gas
CPS300010HG	3000	9.5	688	GX690 Honda Gas
CPS35004HGP	3500	4.0	389	GX390 Honda Gas pull start
CPS35005VC	3500	4.5	479	Vanguard Gas
CPS35005VG	3500	4.5	479	Vanguard Gas
CPS35006VG	3500	5.5	570	Vanguard Gas
CPS50005VG	5000	4.5	627	Vanguard Gas

Specifications may vary, consult factory for custom models

Dimensions: 32"Lx24"Wx27"H (32"Lx31"Wx31"H with optional wheel kit)

Optional Accessories:

Hour meter, Hose reel, Downstream soap injection, Stainless or custom color frame, Wheel kit, Trailer and Tank skid



DISTRIBUTED BY:

2353 Almond Ave. Redlands, CA 92374 phone 800.274.9376 or 1.909.799.9222 www.hydrotek.us fax 909.799.9888 CPS Series 1/15 Hydro Tek ©

