



# **Superior Air Filtration**

Al series units surpass any other on the market with their standard-issue high-grade MERV 8 filters, which capture lint, dust, pollen, dust mites, debris and spores for superior air quality and comfort. Even more powerful filtration is available with an optional MERV 13 filter upgrade.




# **Energy-Efficient Motors**

Powerful, reliable and quiet motors ensure peace of mind while offering performance and durability. PMSM ECM motors also provide up to 60% energy savings compared to other units on the market.

VIRTUO provides you with optimal energy recovery and maximum savings and comfort, while maintaining your property's integrity and value.

### **Controls**

When things are simple, everything is so much easier. Take full control of your Al series air exchanger with simple, easy-to-navigate controls. These stylish and user-friendly controls are designed to blend with most contemporary decors. Available in a range of options, the new controls have the right options to meet your needs.



VTTOUCHW



#### Advanced Touchscreen Control

- Advanced support and information for a greatly enhanced user experience
- Revamped design that blends with contemporary decors like never before
- Variety of font options to change the appearance of the wall control
- Range of flexible options and automatic modes to meet specific needs
- Wireless synchronization with the Deluxe 20-40-60 control for easy installation

### **Technical Features**

SPECIFICATIONS	B110H65RS B110H65RT	B130H65RS B130H65RT B130E65RS B130E65RT	B160H65RS B160H65RT B160E65RS B160E65RT	B150H75NS B150H75NT B150E75NS B150E75NT	B160H75RS B160H75RT B160E75RS B160E75RT
RECOVERY TYPE	HRV	HRV/ERV	HRV/ERV	HRV/ERV	HRV/ERV
CFM AT 0.2 IN. W.G	112 CFM	131 CFM	HRV: 160 CFM ERV: 150 CFM	HRV: 150 CFM ERV: TBD	HRV: 160 CFM ERV: TBD
CFM AT 0.4 IN. W.G.	100 CFM	119 CFM	HRV: 150 CFM ERV: 140 CFM	HRV: 140 CFM ERV: TBD	HRV: 150 CFM ERV: TBD
SRE 32°F   0°C	68% (64 CFM)	HRV: 68% (64 CFM) ERV: 67% (64 CFM)	HRV: 68% (64 CFM) ERV: 67% (64 CFM)	75% (64 CFM)	75% (64 CFM)
SRE -13°F   -25°C	60% (64 CFM)	HRV: 60% (64 CFM) ERV: 56% (64 CFM)	HRV: 60% (64 CFM) ERV: 56% (64 CFM)	60% (64 CFM)	65% (64 CFM)
ASE AT 0°C*	73% (64 CFM)	HRV: 73% (64 CFM) ERV: 72% (64 CFM)	HRV: 73% (64 CFM) ERV: 72% (64 CFM)	HRV: 80% (64 CFM) ERV: TBD	HRV: 80% (64 CFM) ERV: TBD
LATENT RECOVERY / MOISTURE TRANSFER AT 0°C	HRV: N/A	HRV: N/A ERV: 65% (64 CFM)	HRV: N/A ERV: 65% (64 CFM)	HRV: N/A ERV: TBD	HRV: N/A ERV: TBD
VIRTUO AIR TECHNOLOGY	Yes	Yes	Yes	Yes	Yes
MOTOR	ECM PMSM				
FILTRATION	MERV 8 (included), optional MERV 13 (part number V24285)				
DIMENSIONS (H x W x D)	Side ports: 19-1/8 x 23-1/2 x 16-1/8 in.   Top ports: 21-1/2 x 21 x 16-1/8 in.				
PORTS CONFIGURATION	Round, top or side 5 in.	Round, top or side 5 in.	Round, top or side 6 in.	Round, top or side 5 in.	Round, top or side 6 in.
RECIRCULATION	Yes	Yes	Yes	No	Yes
HARDWARE INCLUDED	Drain hose with integrated "snap-in" (HRV only), universal brackets, chains and screws				
WARRANTY	Parts: 5 years   HRV core: limited lifetime   ERV core: 5 years				
ENERGY STAR CERTIFICATION	Yes	HRV: Yes ERV: No	HRV: Yes ERV: No	HRV: Yes ERV: TBD	HRV: Yes ERV: TBD

Authorized dealer \* Data are not HVI certified.



The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Venmar Ventilation ULC is under license. Other trademarks and trade names are those of their respective owners.

