

RX6030/6630/7630

KIOTI UTILITY TRACTOR



run ahead of the pack



ISO 9001
NO:954596



ISO 14001
NO:771475



OHSAS 18001
NO:K033008

Specifications

MODEL		RX6030-AU	RX6630-AU	RX7630-AU
ENGINE				
Model		4B243DTM-A	4F243DTM-A	4F243DTM-A1
Type		4Cyl., In-line Vertical, Water-cooled 4-cycle diesel engine	4Cyl., In-line Vertical, Water-cooled 4-cycle diesel engine	4Cyl., In-line Vertical, Water-cooled 4-cycle diesel engine
Engine gross	HP	60	66	73
Displacement	cc	2,435	2,435	2,435
Rated revolution	rpm	2,600	2,600	2,600
Total displace	cc	2,435	2,435	2,435
Fuel tank capacity	ℓ	85	85	85
DRIVE TRAIN				
Clutch		Dry single stage	Hydro Multi Wet Disc Clutch	Dry single stage
Transmission		Synchro Shuttle Transmission	Synchro Shuttle Transmission	Synchro Shuttle Transmission
Speeds		24 X 24	24 X 24	24 X 24
Differential lock(rear)		Rear Standard	Rear Standard	Rear Standard
Brake		Wet Multi Disc	Wet Multi Disc	Wet disc type
PTO		Hydrostatic, Independent	Independent	Hydrostatic, Independent
Rear PTO(standard)	rpm	540 / 540E	540 / 540E	540 / 540E
HYDRAULIC SYSTEM				
Total Pump capa.(MAX)	ℓ /min	67.6	67.6	72.8
3-point hitch		Category II	Category II	Category II
MAX. lifting capa.(24 behind)	kg	1630	1630(3594)	1768
Hydraulic lift control system		Position, Draft, Mixed Control	Position, Draft, Mixed Control	Position, Draft, Mixed Control
Steering		Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering
TIRE SIZE				
AG Tire	Front	11.2-20	11.2-20	11.2-24
	Rear	14.9-30	14.9-30	16.9-30
Rear	Front	X	X	X
	Rear	X	X	X
Industrial Tire	Front	X	X	X
	Rear	X	X	X
TRAVELING SPEEDS				
Forward	km/h	0.16~36.36	0.16~36.36(0.10~22.59)	0.17~37.86
Reverse	km/h	0.16~35.75	0.16~35.75(0.10~22.21)	0.17~37.23
DIMENSIONS				
Overall length(includes 3-pt hitch)	mm	3,685	3,780	3,715
Overall width(minimum tread)	mm	1,800	1,800	
Wheelbase	mm	2,100	2,100	2,130
Min. ground clearance	mm	420	420	440
Tread	Front	mm	1,465	1,475
	Rear	mm	1,415	1,515

* Note: The specifications are subject to change for the purpose of improvement without any notice

Standard Equipment

- Creep gear
- 4WD
- Auto 4WD
- Rear PTO
- Rear View Mirror
- Parking Brake(RATCHET)
- Horn
- 7 Pin Socket
- Head Lamp(12V 55W/55W)
- Signal Lamp(12V 21W*4EA)
- Backup Light
- PTO Cover
- Cup Holder
- Backup Light
- Rear Remote Hydraulic Valve (No. of Valves : 2, Port : 1/2")
- Joystick valve
- Hydraulic AUTO PTO
- Draft Control

Optional Equipment

- 2nd Remote Hydraulic v/v
- 2nd Remote Hydraulic v/v (Detent)
- 2nd Remote Hydraulic v/v (Detent/Floating)
- 3rd Remote Hydraulic v/v
- 3rd Remote Hydraulic v/v (Detent)
- 3rd Remote Hydraulic v/v (Detent/Floating)
- Rear View Mirror Kit
- Front Weight (8EA)
- Front Weight (10EA) (27kgX10ea)
- Rear Wheel Weight (RX7630) (50kgX2ea)
- Rear Weight (RX6030)(30kgX2ea)
- 3 Pin Socket Kit
- 12V Power Outlet Kit
- Fuel Tank Cap Kit
- Lift Rod Kit
- Turn Control Kit
- Rear Wiper Kit
- Sun Canopy



**Kioti Tractor/
Daedong Industrial. Co., Ltd.**
1422-5, Seocho-Dong, Seocho-Ku, Seoul, Korea
Tel 82-2-3470-7454~9 • Fax 82-2-3470-7485
www.daedong.co.kr

Dealer Imprint Area