



# SAFETY DATA SHEET

J&B PART NUMBER

## 9162

### 1. Identification

**Product identifier** Power Lube® Multi-Purpose Lubricant

**Other means of identification**

**Product code** 05007, 05009, 05011

**Recommended use** Multi-purpose lubricant

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufactured or sold by:**

**Company name** CRC Industries, Inc.  
**Address** 885 Louis Dr.  
Warminster, PA 18974 US

**Telephone**

**General Information** 215-674-4300

**Technical Assistance** 800-521-3168


**Customer Service** 800-272-4620

**24-Hour Emergency** 800-424-9300 (US)

**(CHEMTREC)** 703-527-3887 (International)

**Website** www.crcindustries.com

### 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable liquids	Category 4
<b>Health hazards</b>	Skin corrosion/irritation	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 2
<b>OSHA defined hazards</b>	Not classified.	
<b>Label elements</b>		

**Signal word** Danger

**Hazard statement** Combustible liquid. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life.

**Precautionary statement**

**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Do not breathe mist or vapor. Wear protective gloves/eye protection/face protection. Wash hands thoroughly after handling. Avoid release to the environment.

**Response** If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. In case of fire: Do not use water jet as an extinguisher, as this will spread the fire.

**Storage** Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national regulations.

**Hazard(s) not otherwise classified (HNOC)** None known.

## Supplemental information

33.07% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), Hydrotreated Light		64742-47-8	60 - 70
Distillates (petroleum), Solvent-refined Heavy Paraffinic		64741-88-4	10 - 20
n-Butyl stearate		123-95-5	3 - 5
Fatty Acids, C18-unsatd., Dimers		61788-89-4	1 - 3
Methyl salicylate		119-36-8	1 - 3
Petrolatum		8009-03-8	1 - 3

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
<b>Skin contact</b>	Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
<b>Eye contact</b>	Rinse with water. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.
<b>Most important symptoms/effects, acute and delayed</b>	Direct contact with eyes may cause temporary irritation. Skin irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause redness and pain. Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Alcohol resistant foam. Water spray. Water fog. Dry chemical powder. Dry chemicals. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Water. Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire-fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved.
<b>General fire hazards</b>	Combustible liquid.

### 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	---

**Methods and materials for containment and cleaning up**

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Use water spray to reduce vapors or divert vapor cloud drift. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions**

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

**7. Handling and storage****Precautions for safe handling**

Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Do not breathe mist or vapor. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Avoid contact with clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains. For product usage instructions, please see the product label.

**Conditions for safe storage, including any incompatibilities**

Keep away from heat and sources of ignition. Store in original tightly closed container. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep in an area equipped with sprinklers.

**8. Exposure controls/personal protection****Occupational exposure limits****U.S. - OSHA****Components**

Fatty Acids, C18-unsatd.,  
Dimers (CAS 61788-89-4)

**Type**

TWA

**Value**

5 mg/m<sup>3</sup>

**Form**

Respirable

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)****Components**

Distillates (petroleum),  
Solvent-refined Heavy  
Paraffinic (CAS  
64741-88-4)

**Type**

PEL

**Value**

5 mg/m<sup>3</sup>

**Form**

Mist.

Petrolatum (CAS  
8009-03-8)

PEL

2000 mg/m<sup>3</sup>  
500 ppm  
5 mg/m<sup>3</sup>

Mist.

**ACGIH****Components**

Fatty Acids, C18-unsatd.,  
Dimers (CAS 61788-89-4)

**Type**

STEL

**Value**

10 mg/m<sup>3</sup>

**Form**

Respirable

TWA

5 mg/m<sup>3</sup>

Respirable

**US. ACGIH Threshold Limit Values****Components**

Distillates (petroleum),  
Solvent-refined Heavy  
Paraffinic (CAS  
64741-88-4)

**Type**

TWA

**Value**

5 mg/m<sup>3</sup>

**Form**

Inhalable fraction.

n-Butyl stearate (CAS  
123-95-5)

TWA

10 mg/m<sup>3</sup>

Petrolatum (CAS  
8009-03-8)

TWA

5 mg/m<sup>3</sup>

Inhalable fraction.

**US. NIOSH: Pocket Guide to Chemical Hazards****Components**

Distillates (petroleum),  
Hydrotreated Light (CAS  
64742-47-8)

**Type**

TWA

**Value**

100 mg/m<sup>3</sup>

**Form**

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Distillates (petroleum), Solvent-refined Heavy Paraffinic (CAS 64741-88-4)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Petrolatum (CAS 8009-03-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
<b>Biological limit values</b>	No biological exposure limits noted for the ingredient(s).		
<b>Appropriate engineering controls</b>	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.		
<b>Individual protection measures, such as personal protective equipment</b>			
<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles).		
<b>Skin protection</b>			
<b>Hand protection</b>	Wear protective gloves such as neoprene or nitrile.		
<b>Other</b>	Wear appropriate chemical resistant clothing.		
<b>Respiratory protection</b>	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Wear positive pressure self-contained breathing apparatus (SCBA). Air monitoring is needed to determine actual employee exposure levels.		
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.		
<b>General hygiene considerations</b>	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		

## 9. Physical and chemical properties

### Appearance

<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	Amber.
<b>Odor</b>	Mint.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	-72.4 °F (-58 °C) estimated
<b>Initial boiling point and boiling range</b>	212 °F (100 °C) estimated
<b>Flash point</b>	196 °F (91.1 °C) Tag Closed Cup
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	0.6 % estimated
<b>Flammability limit - upper (%)</b>	5.5 % estimated
<b>Vapor pressure</b>	0.2 hPa estimated
<b>Vapor density</b>	> 1 (air = 1)
<b>Relative density</b>	0.83
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	456.8 °F (236 °C) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity (kinematic)</b>	Not available.

Percent volatile 90.9 % estimated

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Ingestion</b>	May be fatal if swallowed and enters airways.
<b>Inhalation</b>	Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Prolonged inhalation may be harmful. May cause damage to organs by inhalation.
<b>Skin contact</b>	Causes skin irritation.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Skin irritation. May cause redness and pain. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

### Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways. Narcotic effects.

Product	Species	Test Results
Power Lube® Multi-Purpose Lubricant		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	2775.3591 mg/kg estimated
<i>Inhalation</i>		
LC50	Rat	189.8629 mg/l estimated
<i>Oral</i>		
LD50	Rat	5986.6416 mg/kg estimated
<b>Subchronic</b>		
<i>Oral</i>		
LD50	Rat	760.4854 g/kg, 14 days estimated

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Causes skin irritation.
<b>Serious eye damage/eye irritation</b>	Direct contact with eyes may cause temporary irritation.
<b>Respiratory sensitization</b>	Not available.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.
<b>Specific target organ toxicity - single exposure</b>	Narcotic effects.
<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.
<b>Chronic effects</b>	Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure.

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life.

Product	Species		Test Results
Power Lube® Multi-Purpose Lubricant			
<i>Acute</i>			
Fish	LC50	Fish	4814.8149 ppm, 96 hours estimated
Components	Species		Test Results
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)			
<b>Aquatic</b>			
<i>Acute</i>			
Fish	LC50	Bluegill ( <i>Lepomis macrochirus</i> )	2.2 mg/l, 96 hours
Fatty Acids, C18-unsatd., Dimers (CAS 61788-89-4)			
<i>Acute</i>			
Crustacea	NOEL	Daphnia	1000 mg/l, 48 hours loading rate WAF
Fish	NOEL	Fish	1000 mg/l, 96 hours loading rate WAF

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available.

**Partition coefficient n-octanol / water (log Kow)**

Fatty Acids, C18-unsatd., Dimers	1 - 2.5, logKow
Methyl salicylate	2.55

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

**Disposal of waste from residues / unused products** This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty containers may be recycled. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations.

**Hazardous waste code** Not regulated.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

### 14. Transport information

**DOT**

Not regulated as dangerous goods.

**IATA**

Not regulated as dangerous goods.

**IMDG**

Not regulated as dangerous goods.

### 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**SARA 304 Emergency release notification**

Not regulated.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance**

Not listed.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Not listed.

**CERCLA Hazardous Substances: Reportable quantity**

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.**Food and Drug Administration (FDA)** Not regulated.**Superfund Amendments and Reauthorization Act of 1986 (SARA)****Section 311/312** Immediate Hazard - Yes**Hazard categories** Delayed Hazard - Yes

Fire Hazard - Yes

Pressure Hazard - No

Reactivity Hazard - No

**SARA 302 Extremely hazardous substance** No**US state regulations****US. New Jersey RTK - Substances: Listed substance**

None.

**US. Massachusetts RTK - Substance List**

None.

**US. Pennsylvania RTK - Hazardous Substances**

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)

Methyl salicylate (CAS 119-36-8)

**US. Rhode Island RTK**

None.

**US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

**Volatile organic compounds (VOC) regulations****EPA****VOC content (40 CFR 51.100(s))** 100 %**Consumer products (40 CFR 59, Subpt. C)** Not regulated**State****Consumer products** This product is regulated as a Multi-Purpose Lubricant. This product is compliant for use in all 50 states.**VOC content (CA)** 0 %**VOC content (OTC)** 0 %**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information, including date of preparation or last revision****Issue date** 10-29-2013

Material name: Power Lube® Multi-Purpose Lubricant

SDS US

1376 Version #: 01 Issue date: 10-29-2013

7 / 8

<b>Prepared by</b>	Allison Cho
<b>Version #</b>	01
<b>Further information</b>	CRC # 462F
<b>HMSIS® ratings</b>	Health: 1* Flammability: 2 Physical hazard: 0 Personal protection: B
<b>NFPA ratings</b>	Health: 1 Flammability: 2 Instability: 0
<b>Disclaimer</b>	The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.