



**TECHNICAL PRODUCT SPECIFICATIONS
RIGID COMPOSITE VINYL PLANK
PURE**

SPECIFICATIONS:

STYLE NAME:	PURE
RECOMMENDED END USE	RESIDENTIAL, LIGHT COMMERCIAL
FINISH	PREMIUM PROTECT STAIN & SCRATCH RESISTANCE
BACKING	RIGID COMPOSITE BOARD
NOMINAL WEAR LAYER THICKNESS	22 MILS
NOMINAL PRODUCT THICKNESS	5.0 MM
NOMINAL PLANK SIZE	8.03 W X 52.20"L X 0.20" H
PIECES PER CARTON	8
SQUARE FEET PER CARTON	23.25 SQ. FT.
APPROX. WEIGHT PER CARTON	25.68 LBS.
CARTON SIZE	8.82" W X 53.39"L X 1.61"H
CARTONS PER PALLET	56
PALLETS PER CONTAINER	20
SQUARE FEET PER PALLET	1,302.00 SQ. FT.
SQUARE FEET PER 20 FT. CONTAINER	26,040.00 SQ. FT.
APPROX. WEIGHT PER PALLET	1,438 LBS.
APPROX. WEIGHT PER 20 FT. CONTAINER	28,760.00 LBS.
COUNTRY OF ORIGIN	MANUFACTURED IN BELGIUM

PERFORMANCE:

FLOORSCORE CERTIFIED	AATCC 134 (STEP) ELECTROSTATIC 0.4 K.V. OR LOWER
OTHO PHTHALATE FREE	ASTM C1028 SCOF - DRY 0.74
RECLAIMABLE	ASTM F970 STATIC LOAD - PASSES ≤ 1200 LBS.
ASTM E648 CRITICAL RADIANT FLUX - CLASS 1	ASTM F2753 ROLLING LOADS - PASSES
ASTM E662 SMOKE DENSITY - UNDER 450	ASTM F925 CHEMICAL RESISTANCE - PASSES
ASTM F1515 LIGHT STABILITY < 8.0 DELTA E - PASSES	ASTM F1514 HEAT STABILITY DELTA E < 8.0 PASSES
ASTM F2199 DIMENSIONAL STABILITY HEAT - PASSES	ASTM D4060 ABRASION RESISTANCE - 38,000 CYCLES

INSTALLATION:

END USE:	RESIDENTIAL, LIGHT COMMERCIAL
INSTALLATION METHOD:	FLOAT
SUITABLE GRADE LEVEL	ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
RADIANT FLOOR HEAT COMPATIBLE	FLOOR SURFACE TEMPERATURE NOT TO EXCEED 80°F
INSTALLATION SUNDRIES AS REQUIRED:	UNDERLAYMENT NO MORE THAN 1.5 MM THICKNESS

WARRANTIES:

LIFETIME LIMITED RESIDENTIAL WEAR, MANUFACTURING DEFECT, FADE, STAIN, WATERPROOF WARRANTY	10 YEAR LIMITED LIGHT COMMERCIAL WEAR AND MANUFACTURING DEFECT WARRANTY
---	---

DESIGN & MATERIAL NUMBER

EAN/UPC

PART NUMBER

DESIGN & MATERIAL NUMBER	EAN/UPC	PART NUMBER
COLUMBIAN OAK 636M	5414404151629	60000101
COLUMBIAN OAK 226M	5414404157041	60000197
COLUMBIAN OAK 236L	5414404159564	60000211
COLUMBIAN OAK 663D	5414404157058	60000198
TOULON OAK 976M	5414404151735	60000112
TOULON OAK 109S	5414404151698	60000108
TOULON OAK 293M	5414404151759	60000114
TOULON OAK 936L	5414404151728	60000111
TOULON OAK 999D	5414404151773	60000116
LIME OAK 669M	5414404151827	60000121
LIME OAK 693M	5414404151834	60000122
LIME OAK 623M	5414404159571	60000212
LIME OAK 974D	5414404159588	60000213
LIME OAK 954D	5414404157065	60000200
LIME OAK 966D	5414404151865	60000125
LIME OAK 996D	5414404151858	60000124

CARE & MAINTENANCE:

General maintenance should include placing non-staining walk-off mats at all exterior entrances to reduce tracked in soil. Use a soft bristle broom to sweep or vacuum without a beater bar to remove dirt, grit or sand. For heavily soiled areas, use a non-abrasive neutral pH cleaner with a microfiber mop.

877.362.5562
One Beauflor Way
White, GA 30184
United States
beauflor.com