



Experience the benefits of soft water with the efficiency of The Windsor Series



The Windsor Series

Features:

- ◆ Demand initiated regeneration with variable reserve capacity automatically adjusts to your family's changing water use and regenerates only as needed.
- ◆ Double backwash insures maximum regeneration efficiency.
- ◆ Easily adjustable regeneration cycle times for water conservation.
- ◆ Adjustable for a variety of water treatment conditions including settings for hardness, capacity, and time of regeneration.
- ◆ Digital display for time of day and gallons remaining.
- ◆ Advanced electronics with history and diagnostics features for:
 - Days since last regeneration
 - Gallons since last regeneration
 - Current flow rate
 - 7 day peak flow rate
 - 7 day reserve capacity history
 - 63 day water use history
- ◆ All memory is permanently retained in the event of a power outage with no reprogramming and no battery back-up required.

SPECIFICATIONS

MODEL	Mineral Tank Inches	Brine Tank Inches	Salt Storage Lbs.	Shipping Weight Lbs.	WS-1.0 Meter Inches
WS-16	7 x 44	18 x 33	200	75	1.0"
WS-24	8 x 44	18 x 33	200	85	1.0"
WS-32	9 x 48	18 x 33	200	105	1.0"
WS-48	10 x 54	18 x 33	170	140	1.0"
WS-64	12 x 48	18 x 40	300	240	1.0"
WS-96	14 x 65	24 x 41	525	295	1.0"
WS-128	16 x 65	24 x 41	510	395	1.0"
WS-160	22 x 60	24 x 50	510	525	1.0"

CAPACITY CHART


MODEL	Gravel Lbs.	Resin Cu. Ft.	Rated Capacity Low Salt Grains @ Lbs.	Rated Capacity Medium Salt Grains @ Lbs.	Rated Capacity High Salt Grains @ Lbs.	Flow Rate Cont. 10 PSI Drop	Flow Rate Cont. 15 PSI Drop	BKW GPM
WS-16	06	0.50	9,013 @ 2.00	14,039 @ 4.75	16,435 @ 7.50	7.00	9.75	1.3
WS-24	08	0.75	13,520 @ 3.00	21,058 @ 7.13	24,652 @ 11.25	8.00	11.0	1.7
WS-32	09	1.00	18,027 @ 4.00	28,077 @ 9.50	32,869 @ 15.00	9.00	12.5	2.2
WS-48	12	1.50	27,040 @ 6.00	42,116 @ 14.25	48,304 @ 22.50	9.50	13.1	2.7
WS-64	25	2.00	36,053 @ 8.00	56,154 @ 19.00	65,738 @ 30.00	12.0	16.4	3.2
WS-96	39	3.00	54,080 @ 12.00	84,231 @ 28.50	98,608 @ 45.00	13.2	18.0	5.3
WS-128	50	4.00	72,107 @ 16.00	112,308 @ 38.00	131,477 @ 60.00	14.8	19.8	6.5
WS-160	80	5.00	90,134 @ 20.00	140,385 @ 47.50	164,346 @ 75.00	18.0	23.2	10.0

OPERATING CONDITIONS

1. Temperature not to exceed 110°F and should not be subject to freezing.
2. Water pressure, minimum 25 PSI and maximum 120 PSI.

WARRANTY

- 5 YEARS — ALL PARTS
- 5 YEARS — MINERAL TANK
- 5 YEARS — BRINE TANK



DIMENSIONS				
MODEL	A	B	C	D
WS-16	18	33	7	54
WS-24	18	33	8	54
WS-32	18	33	9	58
WS-48	18	33	10	64
WS-64	18	40	12	58
WS-96	24	41	14	75
WS-128	24	41	16	75
WS-160	24	50	22	71

DEALER



"SINCE 1936"



MANUFACTURED BY:
CAPITAL WATER SOFTENER, INC.
 4909 TRIANGLE STREET
 MCFARLAND, WI 53558

608-241-1511