



NEW PRODUCT

Jan. 23, 2019




Manufacturing Valvetrain For 80-Years & 2-Generations

AVAILABLE NOW

Applications	Can Am®
Years	2017-2018
Models	Maverick X3

Valve Spring Kit • Beehive

	KPMI P/N	Type	Max Valve Lift		Installed Height		Seat Pressure		Open Pressure		@ Lift
	91-91300	Intake	.350"		1.180"		60#		161#		.350"
		Exhaust									
	Kit Includes			12	CrSi Valve Springs	12	Titanium Retainers		12	Viton® Seals	

Note: KPMI® made OEM replacement seals are included for a more complete performance valvetrain solution.

Valves • White Diamond® • Hard Chrome Stems • Inconel®



	KPMI P/N	Type	Head Diameter		Stem Diameter	Tulip	O. L.	Material
	91-91312H	Intake	29.01mm	1.142"	0.1960"	15°	3.305"	Stainless
		Standard						
	*91-91316K	Exhaust	25.00mm	0.984"	0.1955"	15°	3.345"	Inconel®
		Standard						

*Inconel® is classified as a "Super Alloy", meaning that it is designed to survive under the most extreme temperatures and pressures where other valves will begin to burn, corrode, or completely fail. This is the material of choice for high output engines running turbos, superchargers, nitromethane, or nitrous. Also, It's recommended for Turbos.

Valve Guides • Manganese Bronze

		A	B	C	D	E	F	G	Intake	Exhaust	ETA
		0.290"	0.340"	0.850"	1.010"	0.490"	0.1955"	0.3565" / Std.	91-91320M		30 days
								+0.001"	91-91321M		30 days
								+0.002"	91-91322M		30 days
								+0.010"	91-91329M		30 days

Valve Guide Seals • OEM Replacement • Tophat

Stem Diameter	O.L.	Seal O.D.	Seal Style	Designed for these guide specs				Type
5.0mm	0.460"	0.975"	3	A	B	C	Spring shoulder Ø	Intake
				0.355 ± 0.005	---	0.290"	0.674"	Exhaust
		Part Number	Quantity	Quantity Discount		ETA		
		71047-4	Pkg. of 4	0%		60 days		
		71047-8	Pkg. of 8	0%		60 days		
		71047-12	Pkg. of 12	0%		60 days		
		71047-16	Pkg. of 16	Less- 10%		60 days		
		71047-50	Pkg. of 50	Less- 15%		60 days		
		71047-100	Pkg. of 100	Less- 20%		60 days		

VISIT US AT WWW.KPMI.US