

"CONVEYING A WORLD OF SOLUTIONS"

Wheel Chocks



MADE IN USA



"CONVEYING A WORLD OF SOLUTIONS"





T. Carson and Company 615 County Line Rd, Suite E Palmer Lake, CO 80133

T. Carson and Company has been providing material handling solutions for more than 25 years. Supplying the mining, cement, aggregate, power and manufacturing industries with quality products to keep production moving and to reduce overall cost per ton.

We offer quality products including rubber and belt repair, belt lacing, skirtboard, wheel chocks, wear products, and much more to customers in the United States, Canada, Mexico, and Central and South America. Our products meet and/or exceed all industry standards.



"CONVEYING A WORLD OF SOLUTIONS"

2 LB. MINI EXTENDED EDGE BASE TCM 376049



| LENGTH | | HEIGHT | |
|--------|--------|--------|---------|
| 8 1/2" | 7 1/2" | 7" | 2.8 lbs |

For Tire Diameters up to 35"
Gross Vehicle Operating Weight up to 30,000
Great for Autos, Trucks, and Trailers

4.5 LB. TRIANGLE WEDGE W/ HANDLE TCM 320040



| LENGTH | WIDTH | HEIGHT | WEIGHT |
|--------|--------|--------|---------|
| 9 3/4" | 8 1/2" | 5 1/4" | 4.5 lbs |

For Tire Diameters up to 32"

Solid Urethane Construction, Durable and Oil Resistant

Embeded Handle Makes Use Quick and Easy

Gross Vehicle Operating Weight 50,000 lbs



"CONVEYING A WORLD OF SOLUTIONS"

Extended Base Wheel Chocks

Solid Urethane Construction Makes Our Chocks Durable and Oil Resistant!
Saftey Orange Color Makes the Chocks Highly Visable and Complies With All
Saftey Regulations

4.5 lb Extended Base Chock TCM 376046



| LENGTH | | HEIGHT | WEIGHT |
|---------|--------|--------|--------|
| 11 1/2" | 8 3/4" | 8 3/4" | 5 lbs |

Good for Tire Diameters up to 46"

Gross Vehicle Operating Weight 60,000 lbs

Convienient Carrying Handle and Rope Hole

6 lb Extended Base Chock
TCM 376047



| LENGTH | WIDTH | HEIGHT | WEIGHT |
|---------|--------|--------|---------|
| 11 1/2" | 8 3/4" | 8 3/4" | 6.4 lbs |

Good for Tire Diameters up to 46"

Gross Vehicle Operating Weight 70,000 lbs

Convienient Carrying Handle and Rope Hole

^{**} Bracket Storage now Available for the 4.5 and 6 lb Models **



"CONVEYING A WORLD OF SOLUTIONS"

Stainless Steel Wheel Chock Bracket (TCM BR46-47)



| LENGTH | WIDTH | HEIGHT | WEIGHT |
|---------|---------|--------|---------|
| 10 7/8" | 10 1/2" | 1 1/2" | 2.6 lbs |

** Now Available from T. Carson and Company **

Stainless Steel Wheel Chock Storage Bracket For Use with 4.5 and 6 lb Chock with Extended Base

4.5lb Extended Base Wheel Chock (TCM376046)

6lb Extended Base Wheel Chock (TCM 376047)





14 Gauge (.075T) A240 304 SS Construction

4 Bolt/Holes for Vehicle Mounting

* Mounting Hardware Not Included *

Extended Base Chocks Easily Slide In for Secure Storage



"CONVEYING A WORLD OF SOLUTIONS"

Ultra high strength, light weight polyurethane wheel chocks for long-term stability and oil resistance. Safety Orange complies with OSHA regulations for many parked vehicles.

The 27 Pound Jumbo (TCM 320038)



| LENGTH | WIDTH | HEIGHT | WEIGHT |
|--|---------|---------|--------|
| 17 1/2" | 14 3/4" | 14 3/4" | 27 lbs |
| Gross Vehicle Operating Weight 140,000 lbs | | | |

Ideal for up to 105 inch wheel diameter





Easy haul handle and convenient rope or chain hole



"CONVEYING A WORLD OF SOLUTIONS"

Ultra high strength, light weight polyurethane wheel chocks for long-term stability and oil resistance. Safety Orange complies with OSHA regulations for many parked vehicles.

70 Ton Large Heavy-Duty Equipment Wheel Chock (TCM 376063)



| LENGTH | WIDTH | HEIGHT | WEIGHT | |
|---|-------|---------|--------|--|
| 15" | 15″ | 10 1/2" | 14 lbs | |
| Up To 70 Ton Payload | | | | |
| Gross Vehicle Operating Weight 245, 000 lbs | | | | |

Ideal for up to 65 inch wheel diameter





Easy haul handle and convenient rope or chain hole



"CONVEYING A WORLD OF SOLUTIONS"

Ultra high strength, light weight polyurethane wheel chocks for long-term stability and oil resistance. Safety Orange complies with OSHA regulations for many parked vehicles.

165 Ton Large Heavy-Duty Equipment Wheel Chock (тсм з76068)



| LENGTH | WIDTH | HEIGHT | WEIGHT |
|-----------------------|--|--------|--------|
| 17 3/4" | 15″ | 9 1/2" | 19 lbs |
| Up To 165 Ton Payload | | | |
| Gross Veh | Gross Vehicle Operating Weight 550,000 lbs | | |

Ideal for up to 105 inch wheel diameter





Easy haul handle and convenient rope or chain hole



"CONVEYING A WORLD OF SOLUTIONS"

Ultra high strength, light weight polyurethane wheel chocks for long-term stability and oil resistance. Safety Orange complies with OSHA regulations for many parked vehicles.

255 Ton Large Heavy-Duty Equipment Wheel Chock (TCM 376053)



| LENGTH | WIDTH | HEIGHT | WEIGHT | |
|--|-------|--------|--------|--|
| 22" | 15″ | 10" | 24 lbs | |
| Up To 255 Ton Payload | | | | |
| Gross Vehicle Operating Weight 866,000 lbs | | | | |

Ideal for up to 142 inch wheel diameter





Easy haul handle and convenient rope or chain hole



"CONVEYING A WORLD OF SOLUTIONS"

Ultra high strength, light weight polyurethane wheel chocks for long-term stability and oil resistance. Safety Orange complies with OSHA regulations for many parked vehicles.

400 Ton Large Heavy-Duty Equipment Wheel Chock (TCM 376064)



| LENGTH | WIDTH | HEIGHT | WEIGHT |
|-----------------------|---------------|---------------|-------------|
| 24 1/2" | 14" | 15 3/4" | 32 lbs |
| Up To 400 Ton Payload | | | |
| Gross Veh | icle Operatir | ng Weight 1,6 | 500,000 lbs |

Ideal for up to 165 inch wheel diameter





Easy haul handle and convenient rope or chain hole



"CONVEYING A WORLD OF SOLUTIONS"

Urethane Wheel Chock Ratings

Standard Chocks

TCM 376049 2 LB. MINI EXTENDED EDGE BASE

| Tire Diameter | up to 35" |
|---------------|-------------|
| GVWR | 30,000 lbs. |

TCM 320040 4.5 LB. TRIANGLE WEDGE W/ HANDLE

| Tire Diameter | up to 32" |
|---------------|-------------|
| GVWR | 50,000 lbs. |

TCM 376046 4.5 LB. STD. EXTENDED EDGE BASE

| Tire Diameter | up to 46" |
|---------------|-------------|
| GVWR | 60,000 lbs. |

TCM 376047 6 LB. STD. EXTENDED EDGE BASE

| Tire Diameter | up to 46" |
|---------------|-------------|
| GVWR | 70,000 lbs. |

Heavy-Duty Equipment Chocks

TCM 320038 27 LB. JUMBO

| Tire Diameter | up to 105" |
|---------------|--------------|
| GVWR | 140,000 lbs. |

TCM 376068 Large Heavy Duty 165 Ton

| Tire Diameter | up to 105" |
|---------------|--------------|
| GVWR | 550,000 lbs. |

TCM 376064 Large Heavy Duty 400 Ton

| Tire Diameter | up to 165" |
|---------------|----------------|
| GVWR | 1,600,000 lbs. |

**GVWR = Gross Vehicle Operating Weight

TCM 376063 Large Heavy Duty 70 Ton

| Tire Diameter | up to 65" |
|---------------|--------------|
| GVWR | 245,000 lbs. |

TCM 376053 Large Heavy Duty 255 Ton

| Tire Diameter | up to 142" |
|---------------|--------------|
| GVWR | 855,000 lbs. |

The Best Performing Chock Ever Tested





"CONVEYING A WORLD OF SOLUTIONS"



Rubber and Urethane Repair

Protect-A-Splice



Belt Lacing

Super Screw, Fix N Go, MS Fasteners

Self-Lock, Clip N Lock

Mini Record, IFS (Invisible Flexible Splice)



Belting

Belt Fabrication



Rubber Skirtboard

Urethane Skirtboard

... Conveyor Accessories, Wear Products and More!