

FPi 5130

Folder Inserter

The FPi 5130 is a breakthrough mailroom advancement for all businesses who process mail. Securely automate and customize your jobs with proven technology. A straight paper path design provides maximum efficiency with media constantly flowing in one direction. This gives the user exceptional processing capabilities, even when feeding multiple sheets from the same tray. The FPi 5130 is capable of inserting into envelope sizes up to 10.5" x 13".

Combined with FlexStream software you can treat every job with the same high level of integrity by controlling every aspect of the mailing process. This machine can be equipped with File-Based Processing, giving the user maximum control at every point in the folding and inserting process. Additional features such as the High Capacity Sheet Feeder, Powered Vertical Exit Stacker and ergonomic, height adjustable tables means the FPi 5130 can be customized into the perfect machine to complement your mailroom needs.





Control Panel

The control panel gives unprecedented ease-of-use, and offers intuitive on screen videos to walk the user through how to load the paper, inserts and envelopes.



Configuration

The FPi 5130 includes a fourfeeder tower. The tower can be customized for envelopes, sheets or inserts. An additional High-Capacity sheet feeder can be added to increase processing capacity and accumulation speed.



Integrity

Document scanning options such as 2D and 1D barcodes and OMR offer the ability to automatically, accurately and securely assemble your sets without the need for manual intervention.

Add-ons

Optional Document Processing Solutions



High-Capacity Sheet Feeder

Add two high capacity sheet feeders. Each feed tray has a document capacity of 1,000 sheets. When productivity is at the heart of what you need, this module is exactly what you need.



Powered Vertical Exit Stacker

The high capacity powered vertical exit stacker is the most common exit for this range of inserters. It holds up to 500 finished envelopes. It is easy to unload on the fly for continuous operation.



Scancode Reading Options:

Automating document processes requires document intelligence. Ensure that documents are accurately assembled, folded and exited correctly with a time and date stamp for each set. FPi 5130 reads scancodes to match documents from different feeders for applications that must have a confirmed match before entering the envelope. The system can match documents and inserts between multiple feed stations.

FlexStream Software

Document Enhancement Solution

FlexStream Software is a document automation solution that gives organizations control over their mailing process. With its unmatched versatility, FlexStream automates and simplifies business workflows. It ensures security and document integrity by adding scancodes that are read by the folder inserter. FlexStream allows the user to choose which documents to print and mail, and which to send electronically.



FlexStream Key Benefits:

- Add Scancodes for variable page processing, document integrity, and verification
- Gain access to USPS® Automation postage rates and discounts
- Correct undeliverable as addressed mail (reduce returned mail)
- Automate processes, reduce labor time and save money
- Organize, sort, group and enhance documents electronically before printing
- Add variable and static marketing text, graphics, logos, QR codes and barcodes





Standard Features

Tower with 4 customizable feeders

Processes envelopes up to 10.5" x 13"

Feeder swap, linking, cascading

May fold documents from different feeders separately

Divert before folding

Process glossy, pre-folded, perforated, and stapled media

Thickness, length and stream feed detection

Automatic setup for up to 24 stored jobs, 18 library jobs, and

8 recently run jobs

5 Fold types (C, Z, V, Double-V, No-Fold)

Envelope Sealing

Powered, Height Adjustable Table

Having a strong stable table increases the life span of equipment and eliminates service activity related to weak, wobbly tables. Increase the life of your investment with a powered height adjustable table that adjusts with a touch of a button for ergonomic operation.



Specifications

Technical Data

Cycling Speed (Max) 4,300 envelopes per hour

Base Dimensions (approx.) (W x L x H) 22.8" x 60" x 31"

Weight 326.5 lbs. 73 dB

Noise emission in dB (REF: ISO 11202)

Tray Capacity

Maximum number of feed stations

High capacity sheet feeders 1,000 sheets

Tower feeders 3 sheet / inserts, 1 envelope

Tower sheet tray 350 each

Tower insert tray 350 (250 Reply Envelopes) Tower envelope tray 250 envelopes, 100 flats

Documents and Inserts

High cap. feeder paper size (W x L)

High cap. feeder paper weight

Tower sheet feeder paper size (W x L) $5" \times 5.3"$ to $9.8" \times 14"$

Tower sheet feeder paper weight

Tower insert feeder paper size (W x L) $5" \times 2.8"$ to $9.8" \times 6"$

Tower insert feeder paper weight

Tower envelope feeder sizes (W x L)

8" x 9.1" to 8.5" x 11.7"

20 lb to 24 lb.

16 lb to 44 lb.

16 lb to 44 lb.

Std: 6.4"x 3.5" to 10.5" x 6.5" Flat: 6.4" x 6.5" to 10.5" x 13"

- Specifications subject to change

Options

FlexStream Document Output Software

Integrity options: 2D, 1D, OMR

File-Based Processing

2 High-Capacity Sheet Trays

Process top, bottom and middle address applications Powered Vertical Exit Stacker: up to 500 envelopes

Envelope Marker



Fax:813-870-6808 Phone: 813-870-6805 AutomatedMailroom.com

Learn more at: www.fp-usa.com/fpi-5130

© 2024 FP Mailing Solutions. All Rights Reserved. TM, SM and ® denote trademarks or registered trademarks of Francotyp-Postalia, Inc. The FP™ logo and FP™ Mailing Solutions Product logos are trademarks or registered trademarks of Francotyp-Postalia, Inc.