


Sustainable Coils LLC

Replacement Coil Solutions!

MOBILE HOME COILS

Revision Date: 09/01/2022



COIL MODEL	COIL WEIGHT	A	B	C	F	G	H
1024A-MH	24	18	19 1/2	16 1/2	3/8	3/4	3/4
1036A-MH	30	18	19 1/2	14 1/2	3/8	3/4	3/4
1036A-FED	34	15 3/4	20 5/8	14 1/2	3/8	3/4	3/4
1048A-MH	36	18	19 1/2	18 1/2	3/8	7/8	3/4
1048A-FED	40	15 3/4	20 5/8	18 1/2	3/8	7/8	3/4
1064A-MH	41	18	19 1/2	18 1/2	3/8	7/8	3/4
1448A-MH+4X4	36	18	19 1/2	18 1/2	3/8	7/8	3/4
1449A-MH+4X4	42	18	19 1/2	18 1/2	3/8	7/8	3/4

Hairpin Tube: 3/8" O.D., CU-122 60 helical copper tube, .016 back wall
2,500 PSI burst pressure minimum

Rows/FPI: 2 rows, 14 FPI: 1024A-MH
3 rows, 14 FPI: 1036A-MH, 1048A-MH, 1448A-MH4X4
1036A-FED, 1048A-FED
4 rows, 12 FPI: 1064A-MH, 1449A-MH+4X4

End Plates: Aluminum

Metering: Piston metered for R-410A refrigerant, additional R-22 piston optional

TXV

Refrigerant connections: Pre-swaged

Expanded IRV (cu. In.): 1024A=104.81, 1036A=137.56, 1048A=176.87, 1064A=235.82
1448A-MH+4X4=176.87, 1449A-MH+4X4=235.82

Drain Pan: Nylon resin pans are 5VFR rated and U.V. safe
FED drain pans are metal

Holding Charge: Dry nitrogen

Warranty: Five year replacement

Please visit our website www.SustainableCoils.com for further information regarding our complete product line.