

KR519V

Transport Base

Vacuum Inkjet Base

Professional grade vacuum inkjet base provides leading class print quality for today's high-speed inkjet systems. Modular in design allowing for quick and easy in-line placement with feeders, inserters, and most bindery equipment.

- Extruded aluminium T-slot rails
- 18" wide rollers for better product transfer
- Engineered to reduce vibration

- ✓ *Stainless Steel Tabletop*
- ✓ *Maintenance Free Drive*
- ✓ *No tool set-up*
- ✓ *Heavy Duty*



*Nothing is
Built Like a
Kirk-Rudy*

KR519V

Vacuum Transport Base

Modular designed to be placed in-line with feeders, inserters, folders, and other bindery equipment.

FEATURES:

- Optimized encoder mount and drive
- Toothless belted drive reduces vibration
- Torque limiting drive protects inkjet heads
- Infeed jam detect protects print head
- Pallet jack/fork lift base clearance
- Adjustable monitor/keyboard stand
- Top side belt adjustment
- Quick and easy belt replacement

OPTIONS:

- Divert
- Vacuum control configurations
- Feeder interface
- Conveyor interface with speed up
- Adjustable angle feeder mount
- Belted or infeed registration
- Infeed double detect & jam detect
- UV curing and infrared dryer mounts
- Hydra-lift (5" height adjustment)
- Camera/Verification systems
- Right or left product flow
- Belts widths: .75", 1.25", 3", 10", 18"
- Infeed and outfeed extensions



Optional infeed extension

- Print area lengths: 39", 50", 66", 88"
- Standard dry/cure area length: 32"
- Custom configurations available

DIMENSIONS	INCHES	CENTIMETERS
LENGTH	34, 43, 54, 70, 92	86, 109, 137, 178, 234 cm
WIDTH	45	114
TABLETOP HEIGHT	33.25	84.5

ELECTRICAL REQUIREMENTS			
VOLTAGE	AMPS	PHASE	Hz
110 V	20	1	50/60
220 V	30	1	50/60

PRODUCT CAPACITY		
	MINIMUM	MAXIMUM
WIDTH	1.25" (3.2 cm)	22" (56 cm)
LENGTH	3" (8.9 cm)	17" (43 cm)
THICKNESS	.007" (0.18 mm)	1" (2.5 cm)

SPEED	
MAXIMUM	600 fpm (Optional 1000 fpm)

Speeds dependent on material being fed.
Specifications subject to change.

