



Item NO. LSCB-80WXY

- Output Wattage:**80W**
- Luminous Flux:**10,500Lm**
- Light Source:740pcs 2835 Epistar SMD
- Base: E40/E39(mogul) E27/E26(Medium)
- Input Voltage: 100-300VAC,50/60Hz
- CRI > 80 PF>0.95
- Beam Angle: 360 degree
- IP Rating: IP60
- 10 Sides Shine Out

- Color Temperature: 2700-3200K/4000-4500K/5000-5500K/6000-6700K
- Lifetime: 50,000+ hours
- (No cover) E40:Dia105*11.41in E27:Dia105*10.83in (Cover) E40 Dia105*11.93in E27:Dia105*11.61
- Aluminum fin heat sink built-in+ Sunon Fan+PC Cover
- Body Temperature:<50°C @Ta=25 °C
- CE RoHS certified
- Internal double stage power supply
- Milky cover,clear cover and NO cover options
- Replaces 275W-300W Metal Halide/HPS**

Cover option	1-50pcs	51-300pcs	301-1000pcs
Without Cover	CALL	CALL	CALL
☒	\$4.00 on unit price		
Inner Box:13cm*13cm*34cm NW:0.65kg QTY: 1pc Outer Carton:55cm*44cm*36cm GW:11.7kg QTY: 12pcs			



Item NO. LSCB-100WXY

- Output Wattage:**100W**
- Luminous Flux:**13,000Lm**
- Light Source:760pcs 2835 Epistar SMD
- Base: E40/E39(mogul) E27/E26(Medium)
- Input Voltage: 100-300VAC,50/60Hz
- CRI > 80 PF>0.95
- Beam Angle: 360 degree
- IP Rating: IP60
- 10 Sides Shine Out
- Lifetime: 50,000+ hours

- Color Temperature: 2700-3200K/4000-4500K/5000-5500K/6000-6700K
- (NO Cover) E40:Dia128*11.30in E27:Dia128*11.02in (With Cover) E40:Dia128*11.81in E27:Dia128*11.50in
- Aluminum fin heat sink built-in+ Sunon Fan+PC Cover
- Body Temperature:<50°C @Ta=25 °C
- Internal power supply
- ETL cETL TUV CE RoHS SAA FCC certified
- Milky cover,clear cover and NO cover options
- Replaces 350W-400W Metal Halide/HPS**

Cover option	1-50pcs	51-300pcs	301-1000pcs
Without Cover	CALL	CALL	CALL
☒	\$4.00 on unit price		
Inner Box:15cm*15cm*36cm NW:0.9kg QTY: 1pc Outer Carton:63cm*49cm*40cm GW:14.5kg QTY: 12pcs			




Item NO. LSCB-120WXY
DLC No. LSCB-120WE39WCC

- Output Wattage:**120W**
- Luminous Flux:**15,000Lm**
- Light Source:960pcs 2835 Epistar SMD
- Base: E40/E39(mogul) E27/E26(Medium)
- Input Voltage: 100~300VAC,50/60Hz
- CRI > 80 PF>0.95
- Beam Angle: 360 degree
- IP Rating: IP60
- 10 Sides Shine Out
- Lifetime: 50,000+ hours

- Color Temperature: 2700-3200K/4000-4500K/5000-5500K/6000-6700K
- (NO Cover) E40:Dia128*12.28in E27:Dia128*12.01in (With Cover) E40:Dia128*12.79in E27:Dia128*12.52in
- Aluminum fin heat sink built-in + Sunon FaPC Cover
- Body Temperature:<50°C @Ta=25 °C
- Internal power supply
- ETL cETL TUV CE RoHS SAA FCC certified
- Milky cover,clear cover and NO cover options
- Replaces 400W-450W Metal Halide/HPS**

Cover option	1-50pcs	51-300pcs	301-1000pcs
Without Cover	CALL	CALL	CALL
☒	\$5.00 on unit price		
Inner Box:15cm*15cm*36cm NW:1.0kg QTY: 1pc Outer Carton:63cm*49cm*41cm GW:15.0kg QTY: 12pcs			


Item NO. LSCB-150WXY
DLC No. LSCB-150WE39WCC

- 
1. Output Wattage:**150W**
 2. Luminous Flux:**20,000Lm**
 3. Light Source:1160pcs 2835 Epistar SMD
 4. Base: E40/E39(mogul) E27/E26(Medium)
 5. Input Voltage: 100-300VAC,50/60Hz
 6. CRI > 80 PF>0.95
 7. Beam Angle: 360 degree
 8. IP Rating: IP60
 9. 10 Sides Shine Out
 10. Lifetime: 50,000+ hours

11. Color Temperature:
2700-3200K/4000-4500K/5000-5500K/6000-6700K
12. (NO Cover) E40:Dia128*13.26in E27:Dia128*12.99in
(With Cover) E40:Dia128*350mm E27:Dia128*343mm
13. Aluminum fin built-in+ Sunon Fan+PC Cover
14. Body Temperature:<50°C @Ta=25 °C
15. **Internal power supply**
16. ETL cETL TUV CE RoHS SAA FCC certified
17. **Replaces 450W-500W Metal Halide/HPS**
18. Milky cover,clear cover and NO cover options
19. Dimmable Available(different quote)

Cover option	1-50pcs	51-300pcs	301-1000pcs
Without Cover	CALL	CALL	CALL
With Cover	Add \$6.00 on unit price		
Inner Box:15cm*15cm*39cm NW:1.2kg QTY: 1pc Outer Carton:63cm*49cm*41cm GW:16.5kg QTY: 12pcs			


Item NO. LSCB-180WXY

- 
1. Output Wattage:**180W**
 2. Luminous Flux:**22,000Lm**
 3. Light Source:1260pcs 2835 Epistar SMD
 4. Base: E40/E39(mogul) E27/E26(Medium)
 5. Input Voltage: 100-300VAC,50/60Hz
 6. CRI > 80 PF>0.95
 7. Beam Angle: 360 degree
 8. IP Rating: IP60
 9. 10 Sides Shine Out
 10. Lifetime: 50,000+ hours

11. Color Temperature:
2700-3200K/4000-4500K/5000-5500K/6000-6700K
12. (NO Cover) E40:Dia128*14.05in E27:Dia128*13.78in
(With Cover) E40:Dia128*14.57in E27:Dia128*14.29in
13. Aluminum fin built-in+ Sunon Fan+PC Cover
14. Body Temperature:<50°C @Ta=25 °C
15. Internal power supply
16. ETL cETL TUV CE RoHS SAA FCC certified
17. **Replaces 600W Metal Halide/HPS**
18. Milky cover,clear cover and NO cover options
19. Dimmable Available(different quote)

Cover option	1-50pcs	51-300pcs	301-1000pcs
Without Cover	CALL	CALL	CALL
With Cover	Add \$7.00 on unit price		
Inner Box:15cm*15cm*41cm NW:0.9kg QTY: 1pc Outer Carton:63cm*49cm*43cm GW:16.5kg QTY: 12pcs			

Item NO. LSCB-200WXY

- 
1. Output Wattage:**200W**
 2. Luminous Flux:**24,000Lm**
 3. Light Source:1260pcs 2835 Epistar SMD
 4. Base: E40/E39(mogul) E27/E26(Medium)
 5. Input Voltage: 100-300VAC,50/60Hz
 6. CRI > 80 PF>0.95
 7. Beam Angle: 360 degree
 8. IP Rating: IP60
 9. 10 Sides Shine Out
 10. Lifetime: 50,000+ hours

11. Color Temperature:
2700-3200K/4000-4500K/5000-5500K/6000-6700K
12. (NO Cover) E40:Dia128*14.05in E27:Dia128*13.78in
(With Cover) E40:Dia128*14.57in E27:Dia128*14.29in
13. Aluminum fin built-in+ Sunon Fan+PC Cover
14. Body Temperature:<50°C @Ta=25 °C
15. Internal power supply
16. ETL cETL TUV CE RoHS SAA FCC certified
Replaces 750W Metal Halide/HPS
17. Milky cover,clear cover and NO cover options
18. Dimmable Available(different quote)

Cover option	1-50pcs	51-300pcs	301-1000pcs
Without Cover	CALL	CALL	CALL
With Cover	Add \$8.00 on unit price		
Inner Box:15cm*15cm*41cm NW:0.9kg QTY: 1pc Outer Carton:63cm*49cm*43cm GW:16.5kg QTY: 12pcs			