



®CSC SCREEN PROCESS SUPPLIES SDN. BHD.

No. 14, Jalan Bertam 5, Taman Daya, 81100 Johor Bahru, Johor, Malaysia
Tel : (+60)7-352 5908, (+60)7-355 2908 Fax : (+60)7-355 5908
Email : sales@cscscreen.com Website : www.cscscreen.com

199701016487
(431984-A)

TECHNICAL DATA SHEET

XILICONE REDUCER 3

GENERAL INFORMATION

Xilicone Reducer 3 is an Ink reducer with 100% polymeric organosilicon compound. Xilicone Reducer 3 was formulated for use in CSC Xilicone Series. Xilicone Reducer 3 is being used for reducing viscosity without changing much of the ink performance and the ink flashing properties. It also will not deter much of the ink clarity as well as the dry film tensile strength.

PRODUCT DATA

Physical condition	: Clear Colorless Liquid
Ingredient	: Polymeric organosilicon compound
Active agent	: 100%
Boiling point range	: 160 °C – 200 °C
Storage	: Ambient temperature (≥ 25 °C and ≤ 35 °C)
Precautionary	: Keep away from aerosols, flammable, oxidizing agents, corrosives and from other flammable products.

APPLICATION METHOD

Xilicone Reducer 3 show the best results in reducing viscosity for the whole range CSC Xilicone series ink.

Xilicone Reducer 3 is used when high ink build up are found and it will also not causing any form of color bleed after viscosity has been re-modify.

The recommended dosage for Xilicone Reducer 3 should be 2% to 10% and should not be added more than 15% base on ink weight.

PACKING AND STORAGE

Keep indoors and store in a cool area. Storage recommended at 25°C to 35°C.

20 kg drum & 200kg drum.

***AVOID STORAGE IN DIRECT SUNLIGHT OR IN EXTREME TEMPERATURE CONDITIONS. ***

AVOID STORAGE CLOSE TO STRONG OXIDATION AGENT.