

Performance

| | |
|--|--------------|
| Rated operating load, standard (lbs): | 1,500 |
| Operating load with optional counterweight (lbs): | 1,600 |
| Tipping load, standard (lbs): | 3,000 |
| Height to bucket pin (in): | 112" |
| Dump height @ bucket discharge (in): | 85" |
| Dump reach @ max height (in): | 20" |
| Max dump angle @ full height (deg): | 40° |
| Bucket rollback at ground level (deg): | 96.7° |
| Bucket breakout (lbs): | 4,084 |
| Lift type Radial (R) or Vertical (V): | R |
| Arm lifting force (lbs): | 3,341 |

Drive Train

| | |
|--------------------------------|------------------|
| Max travel speed (mph): | 7.9 |
| Tire size: | 10 x 16.5 |

Dimensions

| | |
|---------------------------------------|-------------|
| Overall length w/bucket (in): | 129" |
| Width over tires (in): | 60" |
| Height to top of ROPS (in): | 77" |
| Ground clearance (in): | 8" |
| Rear angle of departure (deg): | 26° |
| Wheelbase (in): | 39" |

Weight

| | |
|--------------------------------|--------------|
| Operating weight (lbs): | 5,822 |
|--------------------------------|--------------|

Engine

| | |
|--------------------------|---------------|
| Engine make: | Cat |
| Engine model: | C2.2 T |
| Gross power (hp): | 61 |
| Net power (hp): | 56 |