

# Cold Water Electric Direct Drive



Built for all-purpose cleaning, the lightweight and portable CD Series electric model is perfect for homeowners and small industrial jobs where exhaust fumes are prohibited.

To see more online, scan here or go to [www.mitm.com](http://www.mitm.com):



**Pump**

- Forged brass manifold
- Thermal and safety relief valves
- Adjustable low pressure detergent injector

**Motor**

- Totally enclosed fan-cooled electric motor with thermal overload protection
- 35-foot, 15-amp power cord (20-amp on CD-1502 models) with ground fault circuit interrupter, GFCI

**Frame**

- Powder coated steel mounting plate with center balanced lift and four rubber isolators

**Unit Includes:**

- 25-foot x 3/8-inch non-marking hose with quick connects
- Insulated trigger gun with safety lock-off



CD-1502-2MUH

Limited Warranties:

**1 Year**  
Electric Motor



**7 Year**  
Pump

CSA CERTIFIED

NEMA 5-15P,  
15-amp plug

NEMA 5-20P,  
20-amp plug

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	Mi-T-M NO.	UNLOADER	PLUG TYPE	NOZZLES	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CD-1002-3MUH	1000	2.0	1.5 HP, 120V, 1Ø, 12.5A	AR	3-0362	Adjustable pressure	NEMA 5-15P	Variable high/low pressure	36in.	20x11.5x14in.	70 lb.	58 lb.
CD-1002-2MUH*	1000	2.0	1.5 HP, 120V, 1Ø, 12.5A	General	3-0278	Adjustable pressure	NEMA 5-15P	15° high/low pressure	36in.	20x11.5x14in.	71 lb.	66 lb.
CD-1502-3MUH	1500	2.0	2.0 HP, 120V, 1Ø, 17.0A	AR	3-0362	Adjustable pressure	NEMA 5-20P	Variable high/low pressure	36in.	20x11.5x14in.	76 lb.	70 lb.
CD-1502-2MUH*	1500	2.0	2.0 HP, 120V, 1Ø, 17.0A	General	3-0278	Adjustable pressure	NEMA 5-20P	15° high/low pressure	36in.	20x11.5x14in.	76 lb.	70 lb.

\*Pump accepts incoming water up to 175°F.

**Accessories & Options:**

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
18-0370	Rotating nozzle	CD-1502 models	50-0161	High pressure detergent injector	All models
18-0371	Rotating nozzle	CD-1002 models	CX-0030	50-ft. x 3/8-in. non-marking hose	All models