



Wayne - 712-251-7186 /wayne@premierindinc.com  
 Korey - 712-223-7859 /sales@premierindinc.com  
 Sheena-712-212-1432/sheena@premierindinc.com  
 Marisa -712-898-3283/marisa@premierindinc.com

FAX: 605-356-8072

## Single V-Belts

### Classical



Cross Section	In Stock Lengths	Special Order
A, B, C, D	14" to 540"	14" to 600"
AX, BX, CX	15" to 195"	15" to 195"
AK, BK, CK	---	14" to 600"
AL, BL	---	15" to 195"



Classical belts constructed from pre-stretched polyester cord. "X" designates molded cogged construction (AX, BX, CX). "K" designates Thunder Classical V-Belts, heavy-duty belts constructed from aramid tensile cord (AK, BK, CK). "L" designates Breeze Classical V-Belts, belts designed for quiet running (AL, BL). For belt part number, use Inside Circumference (IC). To calculate IC, measure Outside Circumference (OC) and subtract the following: A- subtract 2", B- subtract 3", C- subtract 4", D- subtract 5". For part number on belt over 210" measure OC and subtract the following: B- subtract 1.5", C- subtract 2", D- subtract 2.5". Example: A30= 1/2" wide; 30" IC (32" OC)

### Wedge


Cross Section	In Stock Lengths	Special Order
3V, 5V, 8V	25" to 560"	16" to 600"
3VX, 5VX	21" to 200"	16" to 200"
3VK, 5VK, 8VK	---	20" to 600"



Wedge belts constructed from pre-stretched polyester cord (3V, 5V, 8V). "X" designates molded cogged construction (3VX, 5VX). "K" designates Thunder Wedge V-Belts, heavy-duty belts constructed from aramid tensile cord (3VK, 5VK, 8VK). For part number, use OC measurement to the tenth of an inch. Example: 3V425= 3/8" wide; 42.5" OC

### Metric

Cross Section	In Stock Lengths	Special Order
SPZ, SPA, SPB, SPC	14" to 540"	14" to 600"
SPZX, SPAX, SPBX, SPCX	20" to 195"	17" to 195"



Metric belts constructed from pre-stretched polyester cord (SPZ, SPA, SPB, SPC). "X" designates molded cogged construction (SPZX, SPAX, SPBX, SPCX). For belt part number, use OC and subtract the following values: SPZ- subtract 13mm, SPA- subtract 18mm, SPB- subtract 22mm, SPC- subtract 30mm. Example: SPA1600= 13mm wide; 1618mm OC

### FHP

Cross Section	In Stock Lengths	Special Order
3L, 4L, 5L	14" to 100"	14" to 100"

Fractional Horsepower (FHP) belts constructed from pre-stretched polyester cord (3L, 4L, 5L). For belt part number, use OC measurement to the tenth of an inch. Example: 4L400= 1/2" wide; 40.0" OC



### Special

**Special Design Cut Edge Constructions:** Used for Ag, Lawn & Garden, Appliance and other tough applications. Available in virtually any cross section such as 3L, 4L, 5L, A, HA, SPA, B, HB, SPB, C, HC, SPC, 3V, 5V, 3LX, 4LX, 5LX, AX, HAX, SPAX, BX, HBX, SPBX, CX, HCX, SPCX, 3VX, 5VX or special dimensions. In lengths 20" to 200".

**Special Design Wrapped Constructions:** Available in A, B, C, 3V, 5V, 3L, 4L, 5L cross sections, in lengths 15" to 580". Aramid Cord, Glass Cord, Polyester Cord; outer wrap fabric in normal and low coefficient of friction; special wraps in Blue, White or Black colors.

**BELTS ARE MANUFACTURED BY BESTORQ AND WAREHOUSED IN NEARBY LINCOLN, NE.**

**Enabling us to meet your belt needs quickly**