

- Subaru OHV 4-stroke V-twin engine with five year warranty
- 4 wheel hydraulic brakes
- Double A-Arm front suspension
- Articulated rear swing arm suspension with quad adjustable shocks
- Low oil pressure warning light
- 25" tires for 14" ground clearance (8" to gearbox)
- Oil filled Dana-Spicer Trans Axle with Locking Differential
- 1200 lb. towing capacity
- Available in red, green, black*, white* or camo*

THIS UNIT CAN BE ORDERED AS AN "S" MODEL (LMC4S)



unit shown with optional accessories



unit shown with optional diamond plate aluminum top

When ordered, an "S" variation will come with a steel bed and our patented rear flip seat kit. Go from dump capable steel bed to 2 person rear seat with safety belts in about 10 seconds.

Specifications

MOTOR SIZE	4-Stroke OHV V-twin	DRIVE	Switch Engaged On Demand, 4 Wheel Drive	BED DIMENSIONS	35.25" L x 41.5" W x 11" D
MOTOR TYPE	653cc Subaru	FRONT SUSPENSION	Double A-Arm Front with up to 3" Travel	BED CAPACITY	9.25 cu.ft. / 400 lbs.
SPEED	Up to 24 MPH**	REAR SUSPENSION	Articulated rear swing arm, quad adjustable shocks, with 3" travel	REAR FLIP SEAT	Available when ordered as an "S" model
FUEL CONSUMPTION	Up to 18 MPG**	BRAKE SYSTEM	4 Wheel Hydraulic Disc Front, Hydraulic Drum Rear	TOWING CAPACITY	1200 lbs.
RANGE	Up to 90 miles**	FRONT/REAR TIRES	25" x 11" x 12"	VEHICLE CAPACITY	1500 lbs.
STARTING	12V electric ignition	DIMENSIONS	143" L x 48" W x 75" D	PARKING BRAKE	Hand operated
BATTERY	12V / 360 cca utility class	WHEEL BASE	104"	HEADRESTS	Yes (front & rear)
BACKUP-RECOIL START	No	TURNING RADIUS	12.25' inside radius	UNDER SEAT STORAGE	Yes (front & rear)
SPARK PLUG	NGK BPR4ES	DRY WEIGHT	1254 lbs.	WARRANTY	Engine: 5 years by SUBARU All other components: 1 Year by ASW
FUEL CAPACITY	5.0 gallons	SHIPPING WEIGHT	1254 lbs. (ships uncrated)	SPECIAL FEATURES	3pt lap/shoulder belts front and rear seats for driver and passengers, 35W headlights, polyurethane powder paint, 2" rear receiver hitch, dump bed, bench seating, welded steel frame, 12V auxiliary outlet for accessories
ALTERNATOR	30 amp	BED MATERIAL	Structural foam "Poly Bed" with stake pockets		
LOW OIL SHUTDOWN	Oil Pressure Warning Light				
TRANSMISSION	CVT automatic				
DIFFERENTIAL	Locking				
TRANSAXLE	Gear drive Dana-Spicer oil filled transaxle				

powered by **SUBARU**

* White, black or camo available at additional cost.

** Estimates. Actual top speeds, fuel consumptions and vehicle ranges may vary due to driving conditions, terrain, climate and other extenuating circumstances. Specifications are subject to change without notice.