


Historically when extracting a sample from a target area using the vacuum extract method two types of sampling have been deployed.

Point Sampling: A single intake located at the end of the sample line offering limited area coverage.

Area Sampling: A pipe line having multiple intakes along its length each intake increasing in outer diameter in accordance with its limited length, thereby attempting to ensure equal sampling rates along the full sample line length.

S4S Micropore Balanced Partial Vacuum Sampling

A pipe line made from porous material having a continuous balanced vacuum samples evenly and consistently from the full surface area of the line, thereby enabling reliable even sampling along its full length regardless of line routing, length or number and length of sections / intake cartridge modules.




Application

- Replacement for most fixed systems
- Transportable monitoring
- General atmospheric monitoring
- Fire detection (smoke)
- Gas/fume/particulate sampling

Typical Applications

- General area monitoring
- Storage tank (internal/external)
- Landfill sites
- Pits
- Tunnels
- Towers
- Pipe runs
- Voids
- Supermarkets
- Vehicle sheds
- Cold storage
- Plant / equipment rooms



Micropore sample line is flexible and may be continuous in length, sectional or modular cartridge to fit all applications

Patent Pending EU16275020.2 Design Reg. 6009030

This document is not contractual and the equipment specification may be modified at any time without prior notice.

NOTE: This datasheet is non-contractual

www.sensorsforsafety.co.uk

E: sales@sensorsforsafety.co.uk T: 01423 206360 F: 01423 206370

Sensors for Safety Ltd | Knaresborough Tech Park | Manse Lane | Knaresborough | N.Yorks | HG5 8LF | UK