


Carey Automatic Door, LLC

(203) 267-4278

100% Pneumatic (ALL AIR), Explosion Proof OSX Door Operators

(Formerly known as STANLEY Pneumatic Door Operators)



**No electrical or electronic components.
All moving components manufactured from non-sparking materials.**

Heavy-duty, intrinsically safe pneumatic door operators are ideal for swinging and sliding door panels in hazardous locations. Proven track record for environments with volatile chemicals since 1970!

- Pneumatically controlled from central air supply.
- Entire system driven by pneumatic cylinders and state of the art pneumatic valves contained within Operator case (no separate control box is required).
- Operator cases, covers and slide rods fabricated from high grade stainless steel 300 series corrosion resistant material.
- Intrinsically safe operator can be mounted inside or outside of hazardous room for swinging door applications.
- Seamless integration with Von Duprin pneumatic exit devices (no separate control box required).
- Operator capable of operating doors against wind velocities (and equivalent stack pressures) up to 40 miles per hour.
- Opening and closing action individually controlled by separate built-in pressure regulators, opening and closing valves. Adjustable for pressure and volume for required speed and power.
- Operator to be activated by two pneumatic palm buttons and/or pneumatic pull cords, or low voltage card reader (mounted at safe distance from hazardous zone, by others).
- Activation options: 0-30 second time delay or push to open, doors stay open, push to close.
- Long operating life and minimal maintenance. Both are achieved through simplicity of design, robust construction plus the use of few moving parts.
- For use with Fire Doors, Hollow Metal Doors, Blast Resistant Doors, Stainless Steel Doors

Air power opening with spring closing (single acting) or power closing (double acting) depending on weight of swinging doors, or counterweights for sliding fire doors.

Interlock Door Systems: Provide for opening of one set of doors (or more) and latching of the other set pneumatically to prevent simultaneous opening of both sets of doors (swinging and sliding doors).

**Considered the most intrinsically safe, reliable, durable & cost effective
Automatic Door Operator in the industry since 1970!**

Virtually maintenance free for 20 - 30+ years!

www.careydoor.com

Carey Automatic Door, LLC

(203) 267-4278

100% Pneumatic (ALL AIR), Explosion Proof OSX Door Operator Applications

Single Swinging Doors:

0-1S Pneumatic Operator Packages. For use with single swinging doors in industrial applications. One operator designed to swing a single hinge hung door either IN/PULL or OUT/PUSH. Maximum door opening width is 72”.

Double Swinging Doors:

0-4S Pneumatic Operator Packages. For use with pairs of swinging doors that require complete speed control for varying conditions in industrial applications. Two operators coupled to operate a pair of doors swinging IN/PULL or OUT/PUSH. Maximum door opening width is 144”.

Swinging Fire Door Packages. An automatic fire door package is available and will interface with the single acting 14” stroke operator.

Single Sliding Doors:

0-7 Pneumatic Operator Packages. For use with single sliding doors in industrial applications. Available for labeled fire door applications. For doors that slide either Left or Right of the opening. Maximum door opening width is 96”.

07-D Pneumatic Operator Packages. For use with heavy single sliding doors in industrial applications. Available for labeled fire door applications. For doors that slide either Left or Right of the opening. Maximum door opening width is 144”.

Bi-Part Sliding Doors:

0-9 Pneumatic Operator Packages. For use with pairs of sliding doors in industrial applications. Available for labeled fire door applications. Maximum door opening width is 192”.

09-D Pneumatic Operator Packages. For use with pairs of heavy sliding doors in industrial applications. Not available for labeled fire door applications. Maximum door opening width is 288”.

Carey Automatic Door, LLC

(203) 267-4278

100% Pneumatic (ALL AIR), Explosion Proof OSX Door Operators

Customers served since 1970!

3M Company
Abbott Pharmaceuticals
Amgen, Inc.
Anagram International
Aspen Aerogels
AstraZeneca Pharmaceuticals
Becton Dickinson
Boehringer Ingelheim Corporation
BOEING
BP Exploration, Inc.
Bristol-Myers Squibb
CordenPharma (Hospira)
Corpus Christi Army Depot
Crane Army Ammunition Activity
Cytex Industries
Dow Corning Corporation
DuPont, Inc. Hospira Pharmaceuticals
Eastman Chemical Company
Estee Lauder
Genzyme Biosurgery
Gilead Sciences
Goodrich Fuel & Utility Systems
Grain Processing
Indiana Michigan Power Company
IST Industrial Summit Technology
Lockheed Martin Corporation
Los Alamos National Laboratory
Mallinckrodt Pharmaceuticals
Markem CIJ Manufacturing
McAlester Army Ammunition Plant
Medtronic (Covidien)
Merck & Co., Pharmaceuticals
MerCruiser
Novartis Consumer Health
Ortho Clinical Diagnostics
Palisades Nuclear Power Plant
Patheon Pharmaceuticals
Philip Morris Company
PPG Aerospace
Raytheon Missile Systems
Regeneron Pharmaceuticals
Sandia National Laboratories
Sigma-Aldrich Corporation
Solvay
The Dow Chemical Company
United Nations Headquarters
Woodward Governor Company
Wright Patterson Air Force Base
Wyeth Ayerst Laboratories
Xerox Corporation