J&B PART NUMBER

38816



Revision Number: 011.0

Issue date: 04/20/2023

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

LOCTITE® 262™ THREADLOCKER

HIGH STRENGTH

Product type/use: Restriction of Use: Anaerobic Sealant None identified

Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

IDH number:

135374

Item number:

26231 United States

Region: Contact information:

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet, www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING:

CAUSES SKIN AND EYE IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR

REPEATED EXPOSURE.

| HAZARD CLASS | HAZARD CATEGORY |
|--|-----------------|
| SKIN IRRITATION | 2 |
| EYE IRRITATION | 2B |
| SKIN SENSITIZATION | 1 |
| SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE | 2 |

PICTOGRAM(S)



Precautionary Statements

Prevention:

Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling

Contaminated work clothing should not be allowed out of the workplace. Wear protective

Response:

IF ON SKIN. Wash with plenty of water IF IN EYES. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical

attention if you feel unwell. If skin irritation or rash occurs. Get medical attention. If eye irritation

persists. Get medical attention. Take off contaminated clothing.

Storage:

Not prescribed

Disposal

Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910 1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s) | CAS Number | Percentage* |
|------------------------|------------|-------------|
| Saccharin | 81-07-2 | 1 - 5 |
| Ethene, homopolymer | 9002-88-4 | 1 - 5 |
| Cumene hydroperoxide | 80-15-9 | 1 - 5 |

IDH number: 135374

Product name LOCTITE® 262™ THREADLOCKER HIGH STRENGTH

Page 1 of 5

Methyl methacrylate 80-62-6 0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. Get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. Wash clothing before reuse. Get medical

attention.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel

Never give anything by mouth to an unconscious person. Get medical

attention.

Symptoms: See Section 11

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. In case of fire, keep containers cool with water spray.

Unusual fire or explosion hazards: Uncontrolled polymerization may occur at high temperatures resulting in

explosions or rupture of storage containers

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen. Irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to

prevent entry into water system; wear full protective equipment during cleanup. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure

Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Keep container closed. Refer to Section 8.

Storage: For safe storage, store between 0 °C (32°F) and 32 °C (89.6 °F)

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|------------------------|--|---|----------------------------------|--------|
| Saccharin | None | None | None | None |
| Ethene, homopolymer | 10 mg/m3 TWA Inhalable particles 3 mg/m3 TWA Respirable particles | 15 MPPCF TWA Respirable fraction 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. | None | None |
| Cumene hydroperoxide | None | None | 1 ppm (6 mg/m3) TWA (SKIN) | None |
| Methyl methacrylate | 50 ppm TWA 100 ppm STEL (Dermal sensitization) | 100 ppm (410 mg/m3) PEL | None | 50 ppm |

Engineering controls:

Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure

limit(s)

Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact. Neoprene gloves

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Color: Odor:

Odor threshold:

pH:

Vapor pressure:

Boiling point/range: Melting point/ range:

Specific gravity: Vapor density: Flash point:

Flammable/Explosive limits - lower:

Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature:

Flammability

Evaporation rate: Solubility in water: Solubility in water:

Partition coefficient (n-octanol/water):

VOC content: Viscosity:

Decomposition temperature:

Liquid

Red Mild

Not available.

Not applicable, Product is non-polar/aprotic.

< 5 mm hg (27 $^{\circ}\text{C}$ (80.6 $^{\circ}\text{F})) <$ 300 mbar (50 $^{\circ}\text{C}$ (122 $^{\circ}\text{F})) no method / method$

unknown < 0.13 mbar (20 °C (68°F))

> 150 °C (> 302°F)

Not applicable. Product is a liquid

1.05 > 1 20 °C

> 100.00 °C (> 212°F) Tagliabue closed cup; No flash point up to 100 °C

Not available Not available Not available

The product is not flammable

Not available Slight Partially soluble Not available

0 %; 0 g/l Not available Not available

10. STABILITY AND REACTIVITY

Stability Stable under normal conditions of storage and use

Hazardous reactions: None under normal processing. Polymerization may occur at elevated temperature or in the

presence of incompatible materials

Hazardous decomposition

Incompatible materials:

products:

Oxides of carbon, Oxides of sulfur, Oxides of nitrogen, Phenolics, Irritating organic vapours

Iron. Copper. Rust. Aluminum. Zinc. Reducing agents. Strong acids and oxidizing agents.

Oxygen scavengers. Strong alkalis.

Reactivity: Not available.

Conditions to avoid: Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from

incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:

Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:

Inhalation of vapors or mists of the product may be irritating to the respiratory system.

Skin contact:

Causes skin irritation. May cause allergic skin reaction.

Eye contact:

Causes eye irritation.

Ingestion:

May cause gastrointestinal tract irritation if swallowed

| Hazardous Component(s) | LD50s and LC50s | Immediate and Delayed Health Effects |
|------------------------|--|--|
| Saccharin | Oral LD50 (Mouse) = 17 g/kg | No Target Organs |
| Ethene, homopolymer | None | No Target Organs |
| Cumene hydroperoxide | None | Allergen, Central nervous system, Corrosive Irritant, Mutagen |
| Methyl methacrylate | Oral LD50 (Rat) = 7,800 mg/kg Oral LD50 (Rabbit) = 6,000 mg/kg Oral LD50 (Rat) = 9,400 mg/kg | Allergen, Irritant, Kidney, Liver, Mutagen, Nervous System, Respiratory |

| Hazardous Component(s) | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|------------------------|----------------|-----------------|---|
| Saccharin | No | No | No |
| Ethene, homopolymer | No | No | No |
| Cumene hydroperoxide | No | No | No |
| Methyl methacrylate | No | No | No |

12. ECOLOGICAL INFORMATION

Ecological information:

Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:

RQ. Environmentally hazardous substance, liquid, n.o.s.

Hazard class or division:

UN 3082

Identification number:

111

Packing group: DOT Hazardous Substance(s):

alpha alpha Dimethylbenzylhydroperoxide

IDH number: 135374

Product name: LOCTITE® 262™ THREADLOCKER HIGH STRENGTH

Page 4 of 5

International Air Transportation (ICAO/IATA)

Proper shipping name:

RQ. Environmentally hazardous substance, liquid, n.o.s.

Hazard class or division:

Identification number: Packing group:

UN 3082 Ш

Water Transportation (IMO/IMDG)

Packing group:

Proper shipping name:

RQ, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazard class or division:

Identification number:

UN 3082 Ш

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:

All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory

TSCA 12 (b) Export Notification:

None above reporting de minimis

CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312:

None above reporting de minimis Immediate Health, Delayed Health

CERCLA/SARA Section 313:

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Saccharin (CAS# 81-07-2). Cumene hydroperoxide (CAS# 80-15-9). Cumene hydroperoxide (CAS# 80-15-9) 10 lbs (4.54 kg)

CERCLA Reportable quantity: California Proposition 65:

This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status:

All components are listed on or are exempt from listing on the Canadian Domestic

Substances List

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 3,8,9,11,13,15

Prepared by:

Product Safety and Regulatory Affairs

Issue date:

04/20/2023

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910 1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.