



Model No.: L5050A36-CX4-12/24

LED Q'ty: 72LEDs/m

PCB Dimension: 500*12*0.22mm









Voltage: DC12V, DC24V

Power Consumption: 23W/m

Waterproof Grade: IP20-IP67

With Four Chips in One LED, available in RGB Warm White, RGB Cool White, RGB Nature White and RGB Amber

Specifications:

Model Number	Color	LED Qty	A(Nm)/(CT:K)	Luminous Flux	PCB Dimensions (mm)	Work Voltage	Power	Water Proof	Packing				
L5050A36-CW4-12/24	 RGB Cool White	72/m	Red : 620-630 Green : 465-470 Blue : 520-525 Yellow : 590-595	Red : 120-140 Green : 110-130 Blue : 300-320 Yellow : 120-140	500*12*0.22	DC12V DC24V	23W/m	NO	5m/reel				
L5050A36-NW4-12/24	 RGB Natural White												
L5050A36-WW4-12/24	 RGB Warm White												
L5050A36-A4-12/24	 RGB Amber												
L5050A36-CW4-12/24	 RGB Cool White	72/m	Blue : 6000-6500K Yellow : 4000-4500K Orange : 3000-3500K	Blue : 420-450 Yellow : 400-420 Orange : 370-390				500*12*0.22		DC12V DC24V	23W/m	IP67	5m/reel
L5050A36-NW4-12/24	 RGB Natural White												
L5050A36-WW4-12/24	 RGB Warm White												
L5050A36-A4-12/24	 RGB Amber												

Features:

1. Input voltage: DC 12V, DC24V
2. Super bright top SMD 5050 LED as lighting sources
3. Different colors are available
4. Every 3-LED are cuttable for 12V strips, 6LEDs are cuttable for DC24V
5. White, Black, Yellow PCB Board are available
6. With 3M adhesive tape on backside

Applications:

1. Decorative lighting for festivals, events, shows, exhibitions
2. Architectural lighting for canopy, corridor, window, archway,
3. Backlight or edge light for signage
4. Path or contour marking
5. Channel letter lighting