



CLASSIC MOUNT PRODUCT CODE: 3-9703

PRODUCT DESCRIPTION

Clear mounting film designed for laminating permanently to printed substrates.

APPLICATIONS

- Adhering nameplates and backlit panels
- Point of purchase displays
- Promotional products
- Temporary graphics

FEATURES AND BENEFITS

- Permanent solvent adhesive on both sides with high peel and good tack.
- Excellent wet out adhesive

TECHNICAL DATA

| | |
|------------------|---------------------------------|
| Face Material | 2.0-mil polypropylene |
| Color and Finish | Clear |
| Adhesive | 22, Permanent solvent each side |
| Liner | 60# bleached kraft differential |

TYPICAL CHARACTERISTICS

| | | |
|--|--------------------------|-------------------------|
| Target Adhesion Values (PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel) | <u>15 min.</u> 30 oz. | <u>24 hr.</u> 40 oz. |
| Static Shear (1/2-inch x 1/2-inch x 500 grams) | > 24 hours | |
| Service Temperature Range | -40°F to +180°F | |
| Shelf Life (@ 73°F, 50% RH) | 1 year | |
| Outdoor Durability | Up to 1 year | |

CHEMICAL RESISTANCE

| | |
|---------------------------------|-----------|
| Distilled Water (24 hr) | No Effect |
| Detergent (24 hr) | No Effect |
| 10% HCl (10 min) | No Effect |
| 10% Ammonium Hydroxide (10 min) | No Effect |
| Anti-Freeze (24 hr) | No Effect |
| SAE 20 Motor Oil (24 hr) | No Effect |
| Gasoline (1 hr) | No Effect |

The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

May-14

Form 108-01(1/99)