

# SAFETY DATA SHEET

# **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

Product Name: Mineral Seal Product Code: 1M230001

**MANUFACTURER ADDRESS:** 

Eastern Oil Company 590 S. Paddock Pontiac, MI 48341 **CHEMTREC (EMERGENCY) PHONE:** 

(800) 424-9300

(202) 483-7616 international

# **SECTION 2: HAZARDS IDENTIFICATION**

**GHS Ratings:** 

Aspiration hazard 1 Aspiration Toxicity Category 1: Known (regarded)- human

evidence - hydrocarbons with kinematic viscosity? 20.5 mm2/s

at 40° C.

**GHS Hazards** 

H304 May be fatal if swallowed and enters airways

**GHS Precautions** 

P331 Do NOT induce vomiting

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P405 Store locked up

P501 Dispose of contents/container appropriately

Signal Word: Danger



# **SECTION 3: COMPOSITION INFORMATION ON INGREDIENTS**

Chemical Name	CAS number	Weight Concentration %
Distillates, petroleum, hydrotreated middle	64742-46-7	90.00% - 100.00%

# **SECTION 4: FIRST AID MEASURES**

### INHALATION:

Remove to fresh air. In severe cases of overexposure, such as with a fire, administer oxygen and seek

SDS for: 1M230001 Page 1 of 5

Printed: 6/9/2016 at 3:53:20PM

qualified medical attention.

#### **EYE CONTACT:**

Flush with copious amounts of water for several minutes. If irritation persists, continue with water application. If, after 15 minutes, irritation continues, seek medical attention.

#### SKIN CONTACT:

Promptly wash skin with mild soap and water.

#### INGESTION:

Do not induce vomiting. Seek qualified medical attention. Small amounts, which may enter the mouth incidental to handling, may be rinsed out with water.

### **SECTION 5: FIRE FIGHTING MEASURES**

Flash Point: > 140 C (>284 F)

LEL: UEL:

#### **FLAMMABLE LIMITS:**

Combustible liquid.

#### **EXTINGUISHING MEDIA:**

Foam, Carbon Dioxide, Dry Chemical, Water Fog

#### **UNUSUAL FIRE AND EXPLOSION HAZARDS:**

Water may spread the fire.

### **SPECIAL FIRE FIGHTING PROCEDURES:**

Water may spread the fire as oil can float on it. Water spray may be used to cool exposed containers.

#### FIRE EQUIPMENT:

Use of water for fire fighting must be done with caution as water may actually spread the fire.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **SPILL OR LEAK PROCEDURES:**

Prevent spill from reaching any type of running or standing water, such as streams, sewers, well water and ponds.

### **SMALL SPILLS:**

For small spills, wipe up or use absorbent to clean the spill area.

#### LARGE SPILLS:

For large spills, pump released material into recovery containers and then spread absorbent over the spill area to collect residuals.

## **SECTION 7: HANDLING AND STORAGE**

#### HANDLING PRECAUTIONS:

When handling, have appropriate safety equipment for the working conditions including eyewash. Do not pressurize, cut, weld, braze, solder, drill, or grind containers containing product residues.

## STORAGE REQUIREMENTS:

Store in a sheltered area, away from temperature extremes in labeled containers. Keep away from heat, sparks, or flame. Avoid contact with eyes, skin, clothing, and shoes.

### **REGULATORY REQUIREMENTS:**

Prevent spread of material to rivers or waterways.

		AND DEDOCMAL	
TELLIUM X.	EXPOSURE CONTROL		PROTECTION
IOLUIION O.	EXI COUNT CONTINO	- AND I LIVOUIAL	

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
-------------------------	----------------------	-----------------------	-----------------------

SDS for: 1M230001 Page 2 of 5

Printed: 6/9/2016 at 3:53:20PM

Distillates, petroleum, hydrotreated middle 64742-46-7

PEL, 5 mg/m3, Mist STEL, 10 mg/m3, Mist TWA, 5 mg/m3, Mist PEL, 5 mg/m3, Mist STEL, 10 mg/m3, Mist TWA, 5 mg/m3, Mist



### **ENGINEERING CONTROLS:**

Good ventilation desirable.

#### **VENTILATION:**

Sufficient to control mists below the operator exposure threshold limit of 5 mg/m3.

#### **WORK HYGIENIC PRACTICES:**

Keep clean. Wash exposed skin areas with mild soap and water.

#### **PROTECTIVE GEAR:**

RESPIRATORY PROTECTION: Required if employee exposure exceeds threshold.

EYE PROTECTION: Where contact is likely, wear safety glasses.

SKIN PROTECTION: Gloves recommended when handling. Neoprene, nitrile, or PVC offers good protection.

#### **CONTAMINATED GEAR:**

Launder contaminated clothing before reuse. Discard of contaminated PPE that cannot be cleaned.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Physical and chmical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the supplier for additional information.

DMSO Extract, IP-346 = <3% by weight

Appearance: Clear

Vapor Pressure: 0.40 2.0

Vapor Density: -99999.0

Specific Gravity: 0.852893887

Freezing point: N/A

Boiling range: N/A

Evaporation rate: Nil

**Explosive Limits: 0%** 

Autoignition temperature: N/A

Viscosity, cSt at 40C: 5

Odor: Mild Hydrocarbon

Odor threshold: N/A

pH: N/A

Melting point: N/A

Solubility: Insoluble

Flash point: 284 F,140 C

Flammability: N/A

Partition coefficient N/A

(n-octanol/water):

Decomposition temperature: N/A

Lbs VOC/Gallon Less Water N/A

### **SECTION 10: STABILITY AND REACTIVITY**

### STABILITY:

STABLE

#### **CONDITIONS TO AVOID:**

Any type of contamination.

No Data Available

## **HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:**

No Data Available

Hazardous polymerization will not occur.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

**Mixture Toxicity** 

SDS for: 1M230001 Page 3 of 5
Printed: 6/9/2016 at 3:53:20PM

Dermal Toxicity LD50: 2,000mg/kg Inhalation Toxicity LC50: 5mg/L

008

**Component Toxicity** 

64742-46-7 Distillates, petroleum, hydrotreated middle

Dermal LD50: 2,000 mg/kg (Rat) Inhalation LC50: 5 mg/L (Rat)

**ROUTES OF ENTRY:** 

Inhalation, Skin Contact, Eye Contact, Ingestion

**Skin Contact** 

No Data Available

**Effects of Overexposure** 

#### **CARCINOGENICITY:**

CAS NumberDescription% WeightCarcinogen RatingNoneNo Data Available

# **SECTION 12: ECOLOGICAL INFORMATION**

### **Component Ecotoxicity**

Distillates, petroleum, hydrotreated middle 96 Hr LC50 Pimephales promelas: 35 mg/L [flow-through]; 96 Hr LC50 Pimephales promelas: >10000 mg/L [static]

# **SECTION 13: DISPOSAL CONSIDERATIONS**

Contact waste hauler for recycling. Follow all Local, State, and Federal regulations.

# **SECTION 14: TRANSPORT INFORMATION**

<u>Agency Proper Shipping Name</u> <u>UN Number Packing Group Hazard Class</u>

DOT Not Regulated

## **SECTION 15: REGULATORY INFORMATION**

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- None

This product is classified under SARA 311/312:

Immediate health (Acute)

The following chemicals are classified under SARA 313 Toxic Release Invetnory (TRI):

- None

Country Regulation All Components Listed

Canada Canadian DSL Yes USA TSCA Yes

SDS for: 1M230001

Page 4 of 5

Printed: 6/9/2016 at 3:53:20PM

# **SECTION 16: OTHER INFORMATION**

#### PREPARATION INFORMATION:

Prepared at an ISO 9001:2008 certified facility.

### **Hazardous Material Information System (HMIS)**

### **National Fire Protection Association (NFPA)**



HMIS & NFPA Hazard Rating Legend


\* = Chronic Health Hazard

0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH



#### DISCLAIMER:

The information presented was obtained from sources believed to be reliable. However, it is provided without any warranty, expressed or implied, regarding its correctness. We do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with the use, handling, storage, or disposal of the product.

Date revised: 2016-06-09 Reviewer Revision 2

Date Prepared: 6/9/2016

SDS for: 1M230001