

JP Composite Series

10, 15, 20 and 30 GPM



POWERED BY
PENTEK[®]



Precision-engineered, corrosion-resistant Composite Pumps in 10, 15, 20 and 30 GPM deliver efficient, dependable performance even in rough, aggressive water. Heads to over 650 feet and capacities to 45 GPM. Built to deliver long-term, trouble-free service.

These pumps feature the proven SignaSeal staging system. Floating impeller design resists sand and reduces sand locking.

APPLICATIONS

- **Water systems...** for residential, industrial, commercial, multiple housing and farm use.

SPECIFICATIONS

Shell – Stainless steel

Diameter – 3-7/8"

Discharge – Fiberglass-reinforced thermoplastic

Discharge Bearing – Nylatron[®]

Intermediate Bearing – (On larger units) Polycarbonate, nitrile rubber and stainless steel

Impellers – Acetal

Diffusers – Polycarbonate

Suction Caps – Polycarbonate with stainless steel insert

Thrust Pads – Proprietary spec.

Shaft and Coupling – Stainless steel

Intake – Fiberglass-reinforced thermoplastic

Intake Screen – Polypropylene

Cable Guard – Stainless steel

Check Valve – Acetal

Agency Listings – CSA

FEATURES

Proven Staging System – Our proven SignaSeal staging system incorporates a harder-than-sand ceramic wear surface that when incorporated with our floating impeller design, greatly reduces problems with abrasives, sand lock-up and running dry.

Discharge – Corrosion-resistant fiberglass reinforced thermoplastic for durability in aggressive water. Large wrench flats for ease of installation.

Discharge Bearing – Exclusive self-lubricating Nylatron[®] bearing resists wear from sand.

Intake – Corrosion-resistant fiberglass reinforced thermoplastic for durability in aggressive water.

Shaft – Positive drive from 7/16" hexagonal heavy-duty 300 grade stainless steel.

Coupling – Stainless steel press fit to pump shaft. Couples to all standard NEMA motors.

Shell – Heavy-walled corrosion-resistant stainless steel. Threaded for easy servicing.

Hardware – All screws, washers and nuts are corrosion-resistant 300 grade stainless steel.

Check Valve – Durable internal poppet type check valve.

Cable Guard – Corrosion-resistant stainless steel guard protects motor leads. Tapered ends prevent pump from catching on well.

Intake Screen – **Corrosion-proof polypropylene.**

Pentek[®] XE Series Motor – 2 and 3 wire NEMA standard all stainless construction water-filled motors.

Nylatron[®] is a registered trademark of Polymer Corp.

All other brand or product names are trademarks or registered marks of Pentair Ltd.

JP Composite Series

10, 15, 20 and 30 GPM


10 Gallons per Minute		PUMP PERFORMANCE (Capacity in Gallons Per Minute)																		
HP	PSI	Pumping Depth in Feet																	Shut-Off Head	
		20	40	60	80	100	125	150	175	200	250	300	350	400	450	500	550	600	Feet	PSI
1/2	0	—	—	14.1	13.5	12.8	12.0	10.8	9.5	7.4	4.7								255	110
	20	14.0	13.3	12.7	12.0	11.0	9.6	7.8	5.2	1.4										
	30	13.2	12.6	11.8	10.9	9.8	8.0	5.5	1.7											
	40	12.4	11.7	10.8	9.7	8.2	8.8	2.0												
	50	11.5	10.5	9.4	7.8	5.8	2.2													
	60	10.4	9.2	7.5	5.4	2.8														
3/4	0	—	—	—	14.8	14.4	13.8	13.0	12.0	11.0	8.4	4.7						340	147	
	20	—	14.7	14.3	13.7	13.0	12.2	11.2	9.9	8.6	5.0									
	30	14.4	14.2	13.7	13.0	12.3	11.2	10.0	8.8	7.2	3.0									
	40	14.2	13.5	12.9	12.1	11.3	10.2	8.9	7.4	5.3										
	50	13.4	12.7	12.0	11.0	10.2	8.9	7.4	5.5	3.2										
	60	12.6	11.9	11.0	10.0	9.1	7.5	5.7	4.4	1.4										
1	0	—	—	—	—	14.9	14.4	13.8	13.3	12.8	11.5	10.1	8.2	5.8	2.1			467	202	
	20	—	—	14.7	14.4	14.0	13.4	12.9	12.3	11.7	10.2	8.3	6.0	2.6						
	30	—	14.7	14.4	13.8	13.4	12.9	12.3	11.7	11.0	9.4	7.4	4.6							
	40	14.6	14.2	13.8	13.3	13.0	12.5	11.8	11.1	10.3	8.5	6.2	3.0							
	50	14.1	13.7	13.3	12.9	12.4	11.8	11.1	10.2	9.5	7.4	4.8								
	60	13.7	13.2	12.8	12.4	11.9	11.2	10.3	9.5	8.7	6.3	3.2								
1-1/2	0	—	—	—	—	—	—	14.7	14.4	14.0	13.2	12.2	11.2	10.1	8.6	7.1	5.2	2.5	636	275
	20	—	—	—	—	14.8	14.4	14.0	13.6	13.2	12.4	11.3	10.2	8.7	7.3	5.3	2.8			
	30	—	—	—	14.7	14.4	14.0	13.6	13.2	12.8	11.9	10.7	9.6	8.1	6.4	4.4				
	40	—	15.0	14.7	14.4	14.1	13.7	13.3	12.8	12.4	11.4	10.2	8.9	7.3	5.5	3.0				
	50	14.9	14.6	14.3	14.0	13.6	13.2	12.8	12.4	12.0	10.8	9.7	8.2	6.5	4.5					
	60	14.5	14.3	14.0	13.6	13.3	12.8	12.4	12.0	11.5	10.2	9.0	7.5	5.6	3.3					

CAUTION: DO NOT use pump at flow rates indicated by the symbol '—'. To do so can cause premature failure of unit. Pump warranty void when failure occurs under these conditions. Tested and rated in accordance with Water Systems Council Standards.


NOTE: Pumps installed with a PRO-Source® tank require a 100 PSI relief valve. Pumps installed with a conventional tank require a 75 PSI relief valve. Relief valve must be capable of relieving entire flow of pump at relief pressure.

JP Composite Series 10, 15, 20 and 30 GPM


PUMP PERFORMANCE - 10 GPM




PUMP PERFORMANCE - 15 GPM



PUMP PERFORMANCE - 20 GPM



PUMP PERFORMANCE - 30 GPM



JP Composite Series

10, 15, 20 and 30 GPM

ORDERING INFORMATION																	
GPM	Motor Type	HP	Stgs	PH	Volt	Assembled Pump			Pump End			Motor		Control Box			
						Catalog Number	Length* Inches	Weight* Pounds	Catalog Number	Length* Inches	Weight* Pounds	Catalog Number	Weight* Pounds	Catalog Number	Weight* Pounds		
10**	2 Wire	1/2	7	1	115	B10P4JP05121	22-3/4	27-1/2	SL10P4CJ	12-3/4	9	P42B0005A1-C	19				
		1/2	7	1	230	B10P4JP05221	22-3/4	27-1/2	SL10P4CJ	12-3/4	9	P42B0005A2-C	19				
		3/4	10	1	230	B10P4JP07221	25-3/4	30-1/2	SL10P4DJ	14-1/2	10	P42B0007A2-C	23				
		1	13	1	230	B10P4JP10221	28-3/4	34-1/2	SL10P4EJ	16	10-3/4	P42B0010A2-C	25				
		1-1/2	17	1	230	B10P4JP15221	34-3/4	41-1/2	SL10P4FJ	19-3/4	12-1/2	P42B0015A2-C	29				
	3 Wire	1/2	7	1	115	B10P4JP05131	22-3/4	27-1/2	SL10P4CJ	12-3/4	9	P43B0005A1-C	19	SMC-IR0511	4		
		1/2	7	1	230	B10P4JP05231	22-3/4	27-1/2	SL10P4CJ	12-3/4	9	P43B0005A2-C	18	SMC-CR0521	4		
		3/4	10	1	230	B10P4JP07231	25-3/4	30-1/2	SL10P4DJ	14-1/2	10	P43B0007A2-C	21	SMC-CR0721	4		
		1	13	1	230	B10P4JP10231	28-3/4	34-1/2	SL10P4EJ	16-1/4	10-3/4	P43B0010A2-C	23	SMC-CR1021	4		
		1	13	3	230				SL10P4EJ	15-1/2	10-1/4	P43B0010A3-C	23				
		1	13	3	460				SL10P4EJ	15-1/2	10-1/4	P43B0010A4-C	23				
		1-1/2	17	1	230	B10P4JP15231	33-1/2	41-1/2	SL10P4FJ	19-3/4	12-1/2	P43B0015A2-C	27	SMC-CR1521	7		
		1-1/2	17	3	230				SL10P4FJ	19-3/4	12-1/2	P43B0015A3-C	23				
		1-1/2	17	3	460				SL10P4FJ	19-3/4	12-1/2	P43B0015A4-C	23				
15**	2 Wire	1/2	5	1	115	B15P4JP05121	22-1/4	27	SL15P4CJ	12-1/4	9	P42B0005A1-C	19				
		1/2	5	1	230	B15P4JP05221	22-1/4	27	SL15P4CJ	12-1/4	9	P42B0005A2-C	19				
		3/4	7	1	230	B15P4JP07221	25-3/4	31	SL15P4DJ	14-1/2	10	P42B0007A2-C	23				
		1	9	1	230	B15P4JP10221	29-1/4	35	SL15P4EJ	16-3/4	11	P42B0010A2-C	25				
		1-1/2	12	1	230	B15P4JP15221	35-1/4	43	SL15P4FJ	20-1/4	13	P42B0015A2-C	29				
	3 Wire	1/2	5	1	115	B15P4JP05131	22-1/4	27	SL15P4CJ	12-1/4	9	P43B0005A1-C	19	SMC-IR0511	4		
		1/2	5	1	230	B15P4JP05231	22-1/4	27	SL15P4CJ	12-1/4	9	P43B0005A2-C	18	SMC-CR0521	4		
		3/4	7	1	230	B15P4JP07231	25-3/4	31	SL15P4DJ	14-1/2	10	P43B0007A2-C	21	SMC-CR0721	4		
		1	9	1	230	B15P4JP10231	29-1/4	35	SL15P4EJ	16-3/4	11	P43B0010A2-C	23	SMC-CR1021	4		
		1	9	3	230				SL15P4EJ	15-1/2	11	P43B0010A3-C	23				
		1	9	3	460				SL15P4EJ	15-1/2	11	P43B0010A4-C	23				
		1-1/2	12	1	230	B15P4JP15231	33-3/4	41	SL15P4FJ	20-1/4	13	P43B0015A2-C	27	SMC-CR1521	7		
		1-1/2	12	3	230				SL15P4FJ	20-1/4	13	P43B0015A3-C	23				
		1-1/2	12	3	460				SL15P4FJ	20-1/4	13	P43B0015A4-C	23				
20**	2 Wire	3/4	5	1	230	B20P4JP07221	23-3/4	30	SL20P4DJ	12-1/2	8-1/2	P42B0007A2-C	23				
		1	7	1	230	B20P4JP10221	27-1/4	34	SL20P4EJ	14-3/4	9-3/4	P42B0010A2-C	25				
		1-1/2	9	1	230	B20P4JP15221	32	39	SL20P4FJ	16-3/4	10-3/4	P42B0015A2-C	29				
		3/4	5	1	230	B20P4JP07231	23-3/4	30	SL20P4DJ	12-1/2	8-1/2	P43B0007A2-C	21			SMC-CR0721	4
		1	7	1	230	B20P4JP10231	27-1/4	34	SL20P4EJ	14-3/4	9-3/4	P43B0010A2-C	23			SMC-CR1021	4
	3 Wire	1	7	3	230				SL20P4EJ	15-1/2	10-1/4	P43B0010A3-C	23				
		1	7	3	460				SL20P4EJ	15-1/2	10-1/4	P43B0010A4-C	23				
		1-1/2	9	1	230	B20P4JP15231	30-1/2	39	SL20P4FJ	16-3/4	10-3/4	P43B0015A2-C	27	SMC-CR1521	7		
		1-1/2	9	3	230				SL20P4FJ	16-3/4	10-3/4	P43B0015A3-C	23				
		1-1/2	9	3	460				SL20P4FJ	16-3/4	10-3/4	P43B0015A4-C	23				
		2	12	1	230				SL20P4GJ	20-1/4	12-1/2	P43B0020A2-C	31	SMC-CR2021	7		
		2	12	3	230				SL20P4GJ	20-1/4	12-1/2	P43B0020A3-C	23				
		2	12	3	460				SL20P4GJ	20-1/4	12-1/2	P43B0020A4-C	23				
		30**	2 Wire	1	5	1	230	B30P4JP10221	26-1/2	35	SL30P4EJ	14	10	P42B0010A2-C	25		
1-1/2	6			1	230	B30P4JP15221	30-1/2	39	SL30P4FJ	15-1/4	11	P42B0015A2-C	29				
3 Wire	1		5	1	230	B30P4JP10231	26-1/2	35	SL30P4EJ	14	10	P43B0010A2-C	23	SMC-CR1021	4		
	1		5	3	230				SL30P4EJ	15-1/2	11	P43B0010A3-C	23				
	1		5	3	460				SL30P4EJ	15-1/2	11	P43B0010A4-C	23				
	1-1/2		6	1	230	B30P4JP15231	29	39	SL30P4FJ	15-1/4	11	P43B0015A2-C	27	SMC-CR1521	7		
	1-1/2		6	3	230				SL30P4FJ	15-1/4	11	P43B0015A3-C	23				
	1-1/2		6	3	460				SL30P4FJ	15-1/4	11	P43B0015A4-C	23				
	2		8	1	230				SL30P4GJ	18-1/4	12	P43B0020A2-C	31	SMC-CR2021	7		
	2		8	3	230				SL30P4GJ	18-1/4	12	P43B0020A3-C	23				
	2		8	3	460				SL30P4GJ	18-1/4	12	P43B0020A4-C	23				


*Length and Weight are approximate.

**For 10 GPM, 15 GPM, 20 GPM, and 30 GPM discharge is 1-1/4" NPT.

NOTE: On 2 HP and larger pumps – Motor, Control Box or Magnetic Starter must be ordered separately.

JP Composite Series 10, 15, 20 and 30 GPM

OUTLINE DIMENSIONS



Discharge	
10 GPM	1-1/4" NPT
15 GPM	1-1/4" NPT
20 GPM	1-1/4" NPT
30 GPM	1-1/4" NPT

For lengths, refer to ordering information tables.

Dimensions (in inches) are for estimating purposes only.