

HTC FL6 Horizontal Turning Center with FADAL 64LP CONTROLLER

Specifications

CAPACITY

Chuck Size (in.)	6
Bar Capacity (in.)	1.77
Max. Turning Dia. (in.)	6.6
Max. Swing Over Saddle (in.)	13
Max. Turning Length (in.)	9.8

SPINDLE

Spindle Motor (hp) (Peak)	10
Spindle Speed (rpm)	6,000
Spindle Nose	A2-5

FEED

Rapid Traverse (ipm)	787
Cutting Feed Rate (ipm)	263
Axis Motor X / Y (hp)	1.7
Axis Ball Screw (dia)	32

TOOLING

Tool Holder	Servo Turret
Number of Tools	12

ACCURACY

Positioning (in.)	0.0002
Repeatability (in.)	0.0001

OTHER

Machine Dimensions LxWxH (in.)	121 x 71 x 62
Machine Weight (lbs)	5,400



Standard Features:

- Bar Feeder Interface
- Chip Conveyor
- Parts Catcher
- 12 Position Servo Turret
- Tool Presetter
- Fully Enclosed
- Automatic Lubrication System
- LED Work Lamp
- Spindle Air Blast
- Rigid Tapping
- Linear Roller Way

Optional Features:

- Bar Feeder



Memory 256mb

2000 blocks/sec Look Ahead

Networking & USB Ports

High Speed Machining