

Cold Water Gasoline Direct Drive

Designed for easy mobility, the high-performance CA Aluminum Series is fitted with our patented vibration isolation plate and is capable of cleaning dirt and grime off any surface.

To see more online, scan here or go to www.mitm.com:



Pump

- Forged brass manifold
- Thermal relief valve
- In-line water strainer

Frame

- Patented vibration isolation plate
- Aluminum frame and base plate with 1/4-inch tube handles
- Flat-free tires

Unit Includes:

- 50-foot x 3/8-inch non-marking hose with quick connects
- Insulated trigger gun with safety lock-off



CA-3003-1MAK

Limited Warranties:

1 Year Mi-T-M Unloader **5 Year** Subaru Engine

3 Year Honda Engine **7 Year** Pump

3 Year Kohler Engine



MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	MI-T-M NO.	UNLOADER	NOZZLES	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CA-2403-1MMH	2400	2.4	196cc Honda OHV	Mi-T-M	3-0353	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	39x20.5x24.5in.	100 lb.	73 lb.
CA-2403-1MMS	2400	2.4	211cc Subaru OHC	Mi-T-M	3-0353	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	39x20.5x24.5in.	100 lb.	73 lb.
CA-2703-1MMH	2700	2.4	196cc Honda OHV	Mi-T-M	3-0353	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	39x20.5x24.5in.	100 lb.	73 lb.
CA-2703-1MMK	2700	2.4	208cc Kohler OHV	Mi-T-M	3-0353	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	39x20.5x24.5in.	100 lb.	73 lb.
CA-2703-1MMS	2700	2.4	211cc Subaru OHC	Mi-T-M	3-0353	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	39x20.5x24.5in.	100 lb.	73 lb.
CA-3003-1MAH	3000	3.0	270cc Honda OHV	AR	3-0389	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	42.5x23.5x24.5in.	155 lb.	105 lb.
CA-3003-1MAK	3000	3.0	277cc Kohler OHV	AR	3-0389	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	42.5x23.5x24.5in.	155 lb.	105 lb.
CA-3003-1MAS	3000	3.0	265cc Subaru OHC	AR	3-0389	Mi-T-M, adjustable pressure	0°, 15° & 25°	36in.	42.5x23.5x24.5in.	155 lb.	105 lb.
CA-3504-1MAH	3500	3.5	389cc Honda OHV	AR	3-0310	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-3504-1MAS	3500	3.5	404cc Subaru OHC	AR	3-0310	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-3504-1MGH*	3500	4.0	389cc Honda OHV	General	3-0350	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-4004-1MAH	4000	3.5	389cc Honda OHV	AR	3-0310	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-4004-1MAK	4000	3.5	429cc Kohler OHV	AR	3-0310	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-4004-1MAS	4000	3.5	404cc Subaru OHC	AR	3-0310	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.
CA-4004-1MGH*	4000	4.0	389cc Honda OHV	General	3-0350	Mi-T-M, adjustable pressure	0°, 15° & 25°	48in.	42.5x23.5x24.5in.	175 lb.	125 lb.

*Model comes standard with external bypass system.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector	All models	CX-0097	External bypass system	2400 to 2700-PSI models
851-0338	50-ft. x 3/8-in. non-marking hose	All models	CX-0098	External bypass system	3500 to 4000-PSI models except 1MGH
AW-8400-0021	Low pressure detergent injector	All models	CX-0099	External bypass system	3000-PSI models
CX-0005	48-in. insulated dual lance	All models			