

® CSC SCREEN PROCESS SUPPLIES SDN. BHD.

No. 14, Jalan Bertam 5, Taman Daya, 81100 Johor Bahru, Johor, Malaysia
Tel : (+60)7-352 5908, (+60)7-355 2908 Fax : (+60)7-355 5908
Email : sales@cscscreen.com Website: www.cscscreen.com

TECHNICAL DATA SHEET

XILICONE PIGMENT CONCENTRATE

GENERAL INFORMATION

Xilicone Pigment Concentrated Paste are high viscosity fine grinded concentrated Pigments Colors in polysiloxane dispersion. Xilicone Pigment Concentrated Paste CSC comes in one component paste color and readily used for all type of silicone paste rubber which include of Xilicone 600 Base, Xilicone Straight UP, Xilicone Matte, Xilicone Puff and all its Catalyst. Xilicone Pigment colors come in ready for mix in 20 liters buckets.


KEY FEATURES

Good flowable viscosity, easy mixing, low screen building, heat accelerated cure and user friendly.

Xilicone PC when mix with bases recommended will not change the low flashing and fast fusing temperature.

Type of Xilicone Pigment Concentrated

1	SI-01	XILICONE PC BLACK BS
2	SI-05	XILICONE PC RED CS 2
3	SI-05/LJ	XILICONE PC RED LJ
4	SI-06	XILICONE PC YELLOW CS 1
5	SI-06/Y2	XILICONE PC YELLOW CS 2
6	SI-07	XILICONE PC BLUE CS 1
7	SI-07/B2	XILICONE PC BLUE CS 2
8	SI-08	XILICONE PC MAGENTA CONC
9	SI-09	XILICONE PC MARINE LJ
10	SI-10	XILICONE PC GREEN BS
11	SI-11	XILICONE PC ORANGE CS1
12	SI-11/2	XILICONE PC ORANGE CS 2
13	SI-12	XILICONE PC VIOLET BW
14	SI-21	XILICONE PC FLUO. YELLOW
15	SI-22	XILICONE PC FLUO.GREEN
16	SI-23	XILICONE PC FLUO. PINK
17	SI-24	XILICONE PC FLUO. VIOLET
18	SI-27	XILICONE PC FLUO. MAGENTA
19	SI-28	XILICONE PC FLUO. BLUE
20	SI-29	XILICONE PC FLUO. RED
21	SI-30	XILICONE PC FLUO. ORANGE



® CSC SCREEN PROCESS SUPPLIES SDN. BHD.

No. 14, Jalan Bertam 5, Taman Daya, 81100 Johor Bahru, Johor, Malaysia ¹⁹⁹⁷⁰¹⁰¹⁶⁴⁸⁷
Tel : (+60)7-352 5908, (+60)7-355 2908 Fax : (+60)7-355 5908 (431984-A)
Email : sales@cscscreen.com Website : www.cscscreen.com

APPLICATION METHOD

- Always mix Bases with Catalyst at the ratio of 1:1 before adding Xilicone Pigment.
- Never use more than 5% Xilicone Pigment Concentrate in any formulations.
- Use turnabout mixer to mix ink well prior usage.

OTHER IMPORTANT TIPS

Never use ink that had been mix with catalyst that had been kept for more than 8 hours.

****STORE INK AWAY FROM HEAT AND LIGHT SOURCE****

Info: 11.13.14

