

CONSTANT LATCHING FLUSH BOLT



TOP BOLT



BOTTOM BOLT

- Constant latching - inactive door remains latched until the active door is opened, releasing the automatic bottom bolt and then the top bolt can be manually released
- Inactive door will relatch automatically when closed
- Low actuation forces
- Fits standard ANSI A115.4 door and frame preparations
- Non-handed
- 3/4" bolt throw with a 7/8" vertical adjustment
- 3/4" backset
- Standard rod length is 12", which is measured from the center of the flush bolt body to the bolt tip
- Body size: 1" W x 6-3/4" L x 2" D
- Meets ANSI A156.3 type 27
- UL listed 3 hr fire doors 8'0" x 10'0"

MFG #	DESCRIPTION	EZ #
FB51P US32D	Metal Door Flush Bolt Set	091025

SURFACE BOLTS



LOCKING
BOTTOM STRIKE



LOCKING
TOP STRIKE

NON-LOCKING
BOTTOM STRIKE



NON-LOCKING
TOP STRIKE

- Standard surface bolt has 1" throw for maximum security
- Ideal for all types of doors
- Fully concealed mounting prevents vandalism
- Available in locking version: unit locks in both the up and down position - locking bolts are furnished with 2 keys in 4 keying variations
- Units packed with wood and machine screws to meet most field conditions
- Units available with either a universal top strike (T) or a flat bottom strike (B)
- 1630 series is constructed of heavy duty steel
- UL listed up to 3 hours when used on the inactive door of pair up to 8' in height
- Meets ANSI/BHMA A156.16, L84161
- Sex bolts available where required

MFG #	DESCRIPTION	EZ #
SB1630B US2G	Bottom Surface Bolt	035837
SB1630BL US2G	Bottom Surface Bolt (Locking)	035838
SB1630T US2G	Top Surface Bolt	035839
SB1630TL US2G	Top Surface Bolt (Locking)	035840

ROLLER LATCH



- Actuation is simple, closing of the door causes the roller to fall in the depression of the strike, thereby holding the door closed
- The projection of the roller is easily adjusted using adjusting screws on the face of the unit
- Maximum projection of the roller is 3/8" allowing for variance in the door clearance
- Nylon roller standard
- Forged brass construction
- Meets ANSI/BHMA A156.16, E19091

MFG #	BODY	STRIKE	EZ #
RL30A626	1" x 3-3/8" x 1-11/16"	1-11/16" x 2-1/4" x 5/32"	035554