# **Super Stock 2021**

## **Rule Questions:**

Billy Estep- 567-230-3608 Jeff 'Fatty' Clark- 614-753-2393 Tim Clark- 740-272-1188

#### **GENERAL**

- Any American-made 1980's & newer full-size cars ONLY.
- Helmet, seat belt, long sleeves/pant and eye protection must be worn at all times on the track.
- Any questions call first. If it doesn't say you can don't do it.
- Cars must be stock unless started otherwise below.
- ABSOLUTELY No painting of the frames.
- Must have a 12" x 12" roof sign that does not strengthen the car in any way.
- Car must be swept clean of debit & glass before coming to event.
- You may use these aftermarket parts: Brake & Gas Pedals, Shifter, Reinforced Tie Rods, Steering Column & Slider Drive Shaft. None of those mentioned may be used to reinforce or strengthen your car.
- JUDGES DECSISON IS FINAL. All cars are subjected to re-inspection at ANY time.

### FRAME AND BUMPERS

- 1. Trailer hitches and braces must be removed. No frame welding other than what is stated in the rules.
- 2. You will be permitted to tilt in one spot of the frames. No seam welding on frames permitted.
- 3. No frame shaping or hammering permitted. You may crease, notch, or dimple rear 12" of the frame to help car roll.
- 4. You may weld the bumper to shock plate and weld the bumper shock where they collapse there must be at least a 1"gap between bumper and frame if using a factory bumper shock. Bumper may be welded directly to frame but if this is done shock must be removed completely. No adding metals. On the back side of bumper where shock mounts you may use a ¼" X 6" X 6" piece of flat metal to create a flat mounting surface. If you hardnose no shortening of the frame.
- 5. Homemade front bumpers are allowed. If you choose to manufacture a homemade bumper, it must conform to the following size limits. It can be no larger than 8"X 8", The point must taper over an area of at least 32" wide and cannot exceed 12" wide (front to back). The point may only extend out 4" from the flat part of the bumper. If using a factory bumper it may be loaded or stuffed full.
- 6. Car must set level bumpers cannot be higher than 22" to bottom of bumper or lower than 15" to bottom of bumper.

## **BODY / CAGE**

- 1. Drivers Door may be welded solid outside seam only. All other doors can be welded 5 on 5 off.
- 2. Deck lids must be in original position above rain channels or they may be removed from car. No wedging. Body creasing is ok. You can weld the trunk 5 on 5 off.
  - 3. Hood can be bolted down with 6 bolts, 2 can go through the front two core supports with all thread (1/2" max all thread.) Hoods must be open for inspection.  $(12" \times 12"$  hole over carburetor).
- 4. Up to 6 factory body bolts may be changed to 1/2" bolts there must be a 1 "gap between body and frame you can use steel spacers, hockey pucks, or stack of washers nothing used may be bigger than 3" in diameter. Body washers inside of car can be no bigger than 3" in diameter.
- 5. If you choose to change the front 2 core support bolts, they count towards your limit of 6 bolts. They may go through the core support to the hood.
- 6. No seam welding will be permitted on body. Repairing sheet metal is limited to where the battery box and gas tank and driver's area of the floorboard of the car.
- 7. Front body space may be 4" tall maximum.
- 8. You may have a bar in the dash area and a bar behind the seat with bars connecting the dash and rear bar on each side. One bar per side connecting front and rear br. Side bars must be inside of car not inside of doors. Roll over bar is permitted No down legs permitted. Gussets permitted in corners of cage must be done at corners only. No bigger than 4" in diameter bars and you can use a ¼" X 10" X 10" plate to attach bars to the sheet metal. No kickers or down legs permitted.
- 9. Dash bar must be 5" from firewall rear bar can be no farther back than where the kick panel meets the seat all bars must be 5" off the transmission tunnel. Gas tank protectors are not permitted. You can have a floating gas tank, but it has to be 5" off the body.
- 10. Original gas tank must be removed and replaced with a boat-type tank or fuel cell. Moved inside of car behind driver's seat but no further back than rear axle.
- 11. Batteries must be moved to passenger side floorboard and securely fastened these must be covered with a rubber or non-flammable material.
- 12. If you use expandable metal, no thicker than 1/8".

#### SUSPENSION

- 1. Tie Rods may be reinforced. Any 5-lug rear end permitted. Cars must be stock unless otherwise noted in rules.
- 2. If you choose to run a watts kit conversion it may be no larger than 6x6 upper mounts and 6x4 lower mounts. You are allowed 1/4" x 2 x 2 square tubing or 2" round pipe for trailing arms.
- 3. You can weld front a-arms down using a ¼" X 2" X 2" piece of steel front and back side of a arm you may also use ¼" X 2" X 2" square tubing or 2" round pipe for rear trailing arms.
- 4. No spacers or other metal permitted in, on top of, or around coil spring inside of frame on front coil springs.
- 5. Rear coil springs may be wired or chained. Solid suspensions are ok. All suspension components must remain factory stock no modifications will be permitted. Cars do not have to bounce. Front coil springs and shocks must remain stock. You may use 1" all thread for rear shocks.
- 6. You can use screw-in spacers to get ride height.
- 7. Leaf spring cars must remain factory springs. You cannot change coil spring to leaf spring set ups.
- 8. Any tire may be used.

## **ENGINE/TRANSMISSION**

- 1. Any car motor of choice is permitted. No chains on engine permitted.
- 2. Angles for cross member cannot be longer than 5" and must be within 12" from factory location.
- 3. You may use any aftermarket ZTR style motor mount. (no flat bar style)
- 4. You may use any Transmission mount.
- 5. Lower engine cradles and pulley protector are allowed. No trans braces or after market bells allowed.

NO OTHER MODIFICATIONS MAY BE MADE TO YOUR CAR UNLESS THEY ARE STATED SPECIFICALLY ABOVE IN THE RULES.

IF YOU STRETCH A RULE, YOU WILL LOSE THAT RULE.

NO WELDING ON FRAME

WE HAVE THE RIGHT TO RE-INSPECT YOUR CAR BY CUTTING OR DRILLING AT ANY TIME. IF YOU ARE CAUGHT BREAKING THE RULES YOU WILL FORFEIT ANY AND ALL WINNINGS YOU ARE AWARDED.

NO REFUNDS ON ILLEGAL CARS.
JUDGES DECISIONS ARE FINAL!!!