



FACILITY NAME:

A Sample Company, Salt Lake City, UT

Hazardous Material Permit Program Report

MSDS #	PRODUCT NAME	Prod #	MFG NAME	MAX LBS OF PROD ON SITE	MAX GAL OF PROD ON SITE	CONTAINER TYPE	LOCATION STORED	LOCATION USED	PHYSICAL STATE	FLASH POINT °F	NFPA	SARA CLASS*	HAZ CLASS:
001	Aluminum Extrusions		Loxcreen Company	674,513.00	0.00	All Shapes	Plant Wide	Plant Wide	Solid		2-0-0	A	
1309-37-1	Iron		0.00000%	0.00	0.00								
1314-13-2	Zinc Oxide		0.00000%	0.00	0.00								
7429-90-5	ALUMINUM (FUME OR DUST)		95.00000%	640,787.35	0.00								
7439-92-1	LEAD		0.00271%	18.29	0.00								
7439-96-5	Manganese		0.00000%	0.00	0.00								
7440-21-3	Silicon		0.60000%	4,047.08	0.00								
7440-47-3	CHROMIUM		0.09000%	607.06	0.00								
7440-48-4	COBALT		0.00000%	0.00	0.00								
017	Aluminum Sheet & Coil 3003		Norandal USA	40,000.00	0.00	Slef Contained	Through Out		Solid				
7429-90-5	ALUMINUM (FUME OR DUST)		99.00000%	39,600.00	0.00								
7439-92-1	LEAD		0.00271%	1.08	0.00								
7439-96-5	Manganese		0.90000%	360.00	0.00								
7440-47-3	CHROMIUM		0.20000%	80.00	0.00								
7440-50-8	COPPER		0.04000%	16.00	0.00								

Prepared by



Using



*SARA CLASS: F=Fire, P=Release of pressure, R=Reactive, A=Acute or immediate, C=Chronic or delayed



FACILITY NAME:

A Sample Company, Salt Lake City, UT

Hazardous Material Permit Program Report

MSDS #	PRODUCT NAME	Prod #	MFG NAME	MAX LBS OF PROD ON SITE	MAX GAL OF PROD ON SITE	CONTAINER TYPE	LOCATION STORED	LOCATION USED	PHYSICAL STATE	FLASH POINT °F	NFPA	SARA CLASS*	HAZ CLASS:
CAS #	CHEMICAL NAME			% OF CHEM:	MAX LBS OF CHEM IN PROD	MAX GAL OF CHEM IN PROD							
7440-66-6	ZINC (FUME OR DUST)			0.40000%	160.00	0.00							
018	Aluminum Welding Wire & Rod		JW Harris Co Inc	500.00	0.00	Boxes	Through Out	Through Out	Solid				
7429-90-5	ALUMINUM (FUME OR DUST)			90.00000%	450.00	0.00							
7439-96-5	Manganese			3.00000%	15.00	0.00							
7440-47-3	CHROMIUM			0.20000%	1.00	0.00							
7440-50-8	COPPER			0.14000%	0.70	0.00							
106	Sulfuric Acid 50%		Industrial	9,000.00	0.00	55gal Drums	Waste Water Treatment#12	Waste Water Treatment#12	Liquid		3-0-2	R,A,C	Corrosive
7664-93-9	Sulfuric Acid (Aerosol forms only)			93.00000%	8,370.00	0.00							
7732-18-5	Water			7.00000%	630.00	0.00							
151	Glycol Ether DB (Butyl Carbitol)		Research/Oxychem	110.00	55gal Metal Drum	Paint Storage	Paint Storage	Paint Storage	Liquid	222	2-1-0	F,A,C	
111-76-2	Glycol Monobutyl Ether			0.50000%	0.55								
112-34-5	2-(2-Butoxyethoxy)-ethanol			99.00000%	108.90								
201	ETCH 828	828	SIC Technologies	35,000.00	0.00	500lb Fiber	Anodize Dept. 12	Anodize Dept. 12	Soild		3-0-2	A	Corrosive
1310-73-2	SODIUM HYDROXIDE			85.00000%	29,750.00	0.00							

Prepared by



Using



*SARA CLASS: F=Fire, P=Release of pressure, R=Reactive, A=Acute or immediate, C=Chronic or delayed



FACILITY NAME:

A Sample Company, Salt Lake City, UT

Hazardous Material Permit Program Report

MSDS #	PRODUCT NAME	Prod #	MFG NAME	MAX LBS OF PROD ON SITE	MAX GAL OF PROD ON SITE	CONTAINER TYPE	LOCATION STORED	LOCATION USED	PHYSICAL STATE	FLASH POINT °F	NFPA	SARA CLASS*	HAZ CLASS:
201.11	Cleaner 3354		Southern Industrial Chemicals	8,800.00	0.00	55gal Plastic Drum	Anodize Dept12/Chemical St	Anodize Dept12/Chemical St	Liquid		3-0-0	A	Corrosive
7664-38-2	PHOSPHORIC ACID		37.50000%	3,300.00	0.00								
205.24	FLPN MM3 GREEN JKG0006	JKG0006	Valspar Corp.	0.00	55.00	5,55gal Metal Drum	Paint Storage		Liquid	70	2-3-0	A, C	Flam/Liq
100-41-4	ETHYL BENZENE		3.00000%	0.00	1.65								
108-65-6	Methoxypropylacetate		17.50000%	0.00	9.63								
108-88-3	TOLUENE		7.50000%	0.00	4.13								
111-76-2	Glycol Monobutyl Ether		15.00000%	0.00	8.25								
112-07-2	Butyl Cellosolve		7.50000%	0.00	4.13								
131-11-3	DIMETHYL PHTHALATE		10.00000%	0.00	5.50								
1330-20-7	XYLENE (MIXED ISOMERS)		7.50000%	0.00	4.13								
14	CHROMIUM COMPOUNDS		20.00000%	0.00	11.00								
205.25	FLNP MM3Brt Blue JKL0006	JKL0006	Valspar Corp.	80.00	220.00	5,55gal Metal Drum	Paint Storage	Paint Storage	Liquid	70	2-3-1	A, C	Flam/Liq
100-41-4	ETHYL BENZENE		3.00000%	2.40	6.60								
100-41-4	ETHYL BENZENE		5.00000%	4.00	11.00								

Prepared by



Using



*SARA CLASS: F=Fire, P=Release of pressure, R=Reactive, A=Acute or immediate, C=Chronic or delayed



FACILITY NAME:

A Sample Company, Salt Lake City, UT

Hazardous Material Permit Program Report

MSDS #	PRODUCT NAME	Prod #	MFG NAME	MAX LBS OF PROD ON SITE	MAX GAL OF PROD ON SITE	CONTAINER TYPE	LOCATION STORED	LOCATION USED	PHYSICAL STATE	FLASH POINT °F	NFPA	SARA CLASS*	HAZ CLASS:
CAS #	CHEMICAL NAME			% OF CHEM:	MAX LBS OF CHEM IN PROD	MAX GAL OF CHEM IN PROD							
108-65-6	Methoxypropylacetate			12.50000%	10.00	27.50							
108-88-3	TOLUENE			12.50000%	10.00	27.50							
111-76-2	Glycol Monobutyl Ether			7.50000%	6.00	16.50							
112-07-2	Butyl Cellosolve			10.00000%	8.00	22.00							
131-11-3	DIMETHYL PHTHALATE			7.50000%	6.00	16.50							
1330-20-7	XYLENE (MIXED ISOMERS)			7.50000%	6.00	16.50							
15	COBALT COMPOUNDS			15.00000%	12.00	33.00							
68187-11-1	Pigment Blue`			12.50000%	10.00	27.50							
205.29	Fluoropon MM3 White JKW0005	JKW0005	Valspar Corp.	0.00	500.00	5,55gal Metal Drum	Paint Storage		Liquid	70	2-3-0	A,C	Flam/Liq
100-41-4	ETHYL BENZENE			2.00000%	0.00	10.00							
108-88-3	TOLUENE			7.50000%	0.00	37.50							
111-76-2	Glycol Monobutyl Ether			4.00000%	0.00	20.00							
112-07-2	Butyl Cellosolve			5.00000%	0.00	25.00							
112-07-2	Butyl Cellosolve			2.00000%	0.00	10.00							
112-34-5	2-(2-Butoxyethoxy)-ethanol			3.00000%	0.00	15.00							

Prepared by



Using



*SARA CLASS: F=Fire, P=Release of pressure, R=Reactive, A=Acute or immediate, C=Chronic or delayed