



# ELEVATION

*Made in Colorado, for Colorado's Climate!*

## Elevation

*Premium 100% Acrylic Finishes*  
1220 Dryfall

### Description

*Elevation 100% Acrylic Flat Dryfall* is a 100% acrylic matte-finish latex paint that is formulated specifically to endure the rigors of Colorado's unique climate. This unique, low-VOC formula is fast drying, allowing for overspray to dry as it falls from ceilings, making for easy clean-up. Available in 1220 white or 1224 black factory colors; special colors are also available upon request.

### Application and Substrate Information

Mix or stir thoroughly before using. Paint should be applied through airless spray equipment (2,000 psi, 0.015" – 0.021" tip). A second coat may be applied at a minimum of 3-4 hours after applying the first coat as drying conditions allow. Brush and roll applications are not recommended due to the fast drying characteristics.

For best results, temperatures (air, surface and material temperatures) should be at or above 50°F (10°C) and at least 5°F above the dew point before applying.

Recommended for ceilings at least 15 ft. to allow overspray to dry before falling to the ground. Should be applied in a well-ventilated under low humidity conditions. Air temperature should be at 50°F or above to ensure good dry-fall characteristics.

### Old Western Paint Co., Inc.

2001 W. Barberry Pl.  
Denver, CO 80204  
Phone: 303-825-5147  
Fax: 303-825-2437  
www.oldwesternpaint.com

### Product Data

Gloss/Sheen (85°)	< 5 units (flat)
VOC Content (g/L)	< 50
Viscosity (Krebs Units)	97 (± 3)
Density (lb/gal)	14.3
Weight Solids	73 %
Volume Solids	52 %
Coverage (1.5 dry film)	450 ft <sup>2</sup> *

\*Theoretical value; may vary based on substrate porosity/application method; practical coverage when used over industrial ceilings including duct work, corrugated metal, and/or multiple cross beams is expected 200-300 square feet per gallon.

### Features and Benefits

- ✓ Designed specifically for Colorado's Climate
- ✓ Excellent hiding power
- ✓ Provides a rich, matte finish
- ✓ Reduced volatile organic content (VOC) levels
- ✓ Does not contain alcohol

### Thinning

Thinning is not required and may inhibit dry-fall characteristics.

### Dry Time

Will dry to touch in one hour or less; may be recoated after four hours. Typical time for full cure is 7 days. Dry-fall characteristics may be affected by poor ventilation, low temperatures, amount of colorant and/or high humidity areas.

### Clean-up

Clean all tools and equipment with warm, soapy water.

### Environmental/Health Considerations

Formulated without lead, mercury, and other heavy metals. Does not contain ethylene glycol. No reportable amount of crystalline silica.



# ELEVATION

*Made in Colorado, for Colorado's Climate!*

**Old Western Paint Co., Inc.**

2001 W. Barberry Pl.  
Denver, CO 80204  
Phone: 303-825-5147  
Fax: 303-825-2437  
[www.oldwesternpaint.com](http://www.oldwesternpaint.com)

## General Surface Preparation

All foreign material, including loose or peeling paint, dirt, grease, oil, wax, chalk, mildew, rust, dust, curing agents, etc., must be removed prior to use. Failing to do so may compromise proper adhesion and overall performance. Caulk all cracks and open seams. Putty all nail holes. An appropriate primer should be used when coating bare or porous substrates. A stain blocking primer is recommended over areas where stains would 'bleed through' to the surface. Glossy surfaces should be dulled prior to coating, and rough or patched surfaces should be sanded.

## Specific Substrate Recommendations

**Siding:** Not recommended.

**Concrete/Masonry Block:** New concrete should cure for at least 30 days prior to priming and painting. The surface pH should be below 10 before applying an alkali resistant primer. Block filler should be used over masonry block.

**Metal:** Product contains a flash-rust inhibitor and may be applied over ferrous metal, zinc-treated metal, or various other metal substrates.

**Drywall/Gypsum Board:** Nails and screws should be countersunk and properly covered using putty or drywall mud, then sanded to be flush with the rest of the surface. Recommended for ceilings only.

**Wood:** Unpainted wood should be sanded smooth, wiped, and primed with an appropriate primer. For redwood or cedar, a stain blocking primer should be used to prevent bleed-through from soluble tannin stains. Recommended for ceilings only.

## Recommended Primers

Concrete/Masonry	1251 Elevation 100% Acrylic Primer
Drywall	0710 Colorado Pro Primer/Sealer
Drywall	0610 Colorado Pro 600 Primer
Metal	1255 Elevation All-Prime
Plaster	1251 Elevation 100% Acrylic Primer
Wood	1251 Elevation 100% Acrylic Primer
Wood (tannin)	1255 Elevation All-Prime
Cement Block	1250 Elevation Block Filler

## Packaging

Available in 5-gallon containers. Actual volume amounts of paint are indicated on the label. Volume is adjusted to account for the addition of colorants.

## Intended Use

To be used in a manner consistent with latex wall paints and finishes. Do not take internally. Keep out of reach of children and pets. Not recommended for floors or where water can puddle. Keep from freezing.

**WARNING:** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC AND MAY CAUSE SERIOUS ILLNESS IF YOU ARE EXPOSED, ESPECIALLY FOR CHILDREN OR THOSE WHO ARE PREGNANT. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to minimize lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. For further information, contact the U.S.E.P.A. National Lead Information Hotline at 1-800-424-LEAD or visit [www.epa.gov/lead](http://www.epa.gov/lead).

## Disclaimer

All information and data appearing in this document are provided in good faith and are believed to be reliable and accurate to the best of our knowledge at the date of publication. None of the provided information is to be considered a warranty or quality specification or all-inclusive and is given only as a guidance. It is the user's responsibility to determine the intended utilization of the product. No guarantee, expressed or implied, is made by Old Western Paint Co., Inc. And the user assumes all risk and responsibility.