


Sustainable Coils LLC

Replacement Coil Solutions!

Nordyne Uncased replacement coil options:

Revision date: 03/10/2021



COIL MODEL	COIL WEIGHT	A	B	C	D	E	F	G	H
RC3BA-24U-A	23	12 3/4	19 1/2	12 1/2	15 1/2	5 1/2	3/8	3/4	3/4
RC3BA-36U-A	38	12 3/4	19 1/2	18 1/2	15 1/2	5 1/2	3/8	3/4	3/4
RC3BA-36U-B	39	18 1/8	19 1/2	18 1/2	15 1/2	10 7/8	3/8	3/4	3/4
RC3BA-48U-B	39	18 1/8	19 1/2	18 1/2	15 1/2	10 7/8	3/8	7/8	3/4
RC3BA-48U-C	40	21 1/16	19 1/2	18 1/2	15 1/2	13 13/16	3/8	7/8	3/4

*Denotes over size coil that must be shipped on a skid to a commercial location.

Suction line: ↑ 14 1/2", → 2 3/8" left side.
 Liquid line: ↑ 12 1/8", → 1 3/8" left side.
 Dual drains: Primary drain → 2" from left corner.

UNIGUARD® by Virtus Precision Tube, 3/8" O.D. CU-422 copper alloy tubing
 2,490 PSI burst pressure minimum
 Aluminum end plates to protect against rust corrosion
 Enhanced aluminum fins spaced at 14 FPI
 Piston metered for original R-22 applications, R-410A piston available upon request
 R-22 and R-410A expansion valve kits available upon request
 22 ga. G-90 paint grip metal drain pan coated for rust protection and painted
 Pre-swaged refrigerant connections; shipped with dry nitrogen holding charge
 Five year replacement warranty

Visit our website www.SustainableCoils.com for further information regarding our complete product line.