SPECIFICATIONS	SN				
	Go-Go® Ultra X	$\text{Go-Go}{}^{\tiny{\odot}}\text{LX}\text{w/}\text{CTS}\text{Suspension}\text{Go-Go}\text{Elite}\text{Traveller}^{\tiny{\otimes}}$		Go-Go® Sport	Go-Chair®
Max. weight capacity: 260 lbs.	260 lbs.	300 lbs.	300 lbs.	325 lbs.	250 lbs.
Maximum speed:1	Up to 4 mph	Up to 4.4 mph	Up to 4 mph	Up to 4 mph	Up to 3.5 mph
Ground clearance: ²	2"	1.5" at motor	2"	3"	1.75"
Turning radius: ²	3W: 33" / 4W: 44"	3W: 33" / 4W: 44.75"	3W: 33" / 4W: 44"	3W: 36" / 4W: 52"	26.75" without foot platform
Overall length: ²	3W: 37" / 4W: 39.5"	3W: 39.75" / 4W: 41"	3W: 37" / 4W: 39.5"	3W: 43" / 4W: 43"	29" without foot platform
Overall width: ²	19.5"	20.5"	19.5"	20"	19"
Battery charger:	Off-board, 2 amp	Off-board, 2 amp	Off-board, 2 amp	Off-board, 2 amp	Off-board, 2 amp
Per-charge range: ^{1,5} Up to 8 miles	Up to 8 miles	3W: Up to 9.44 miles	3W. Up to 7.2 miles ⁸ 4W. Up to 7.7 miles	3W: Up to 9 miles 4W: Up to 12 miles³	Up to 8 miles
Battery weight ⁴ :	9 lbs. each ⁶	14 lbs. each ⁷	14 lbs. each7	14 lbs. each ⁷	20 lbs. (battery pack)
Batteries (2 required) ³ ; 12 AH (12V, deep cycle)	3, 12 AH	18 AH	18 AH	18 AH	12 AH
Weight w/o battery pack ² 3-wheel: 72 lbs. 4-wheel: 78.5 lb	² 3-wheel: 72 lbs. 4-wheel: 78.5 lbs.	3-wheel: 85.4 lbs. 4-wheel: 87.4 lbs.	3-wheel: 75 lbs. 4-wheel: 78.5 lbs.	3-wheel: 84 lbs. 4-wheel: 87 lbs.	86 lbs.
Heaviest piece: ²	3-wheel: 29.5 lbs. (front section) 4-wheel: 34 lbs. (front section)	3-wheel: 34 lbs. (front section) 4-wheel: 36.6 lbs. (front section)	3-wheel: 34 lbs. (front section) 3-wheel: 29.5 lbs. (front section) 3-wheel: 36.2 lbs. (front section) 4-wheel: 36.6 lbs. (front section) 4-wheel: 34 lbs. (front section) 4-wheel: 36.2 lbs. (front section)	3-wheel: 29.5 lbs. (front section) 3-wheel: 36.2 lbs. (rear section) 4-wheel: 34 lbs. (front section) 4-wheel: 52.2 lbs. (front section)	34 lbs. (rear section)

 1 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. This specification can be subject to a variance of (+ or -) 10%.

²Due to manufacturing tolerances and continued product improvement, this specification is subject to a variance of +/- 3%. ³AGM or gel-cell type recommended.

⁴Battery weight may vary based on manufacturer.

Flested in accordance with ANSI/RESNA, WC Vol 2, Section 4, and ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity. 612 AH battery pack weight is 18 lbs.

718 AH battery pack weight is 28 lbs.

⁸ Range tested with 12AH batteries.

The information contained herein is correct at the time of publication. We reserve the right to alter specifications without prior notice.



Dealer Information









- Feather-touch disassembly permits simple frame separation with only one hand
- Pride®'s exclusive black, non-scuffing tires
- Auto-connecting front to rear cable





- **FEATURES**
- CTS Suspension (Comfort-Trac front and rear independent suspension)
- Feather-touch disassembly permits simple frame separation with only one hand
- Includes 2 sets of easily changeable colored panels in Red and Blue
- Pride®'s exclusive black, non-scuffing tires
- · Auto-connecting front to rear cable





- Feather-touch disassembly permits simple frame separation with only one hand
- Pride®'s exclusive black, non-scuffing tires
- Auto-connecting front to rear cable
- Includes two sets of easily changeable colored panels in two exciting colors -Red and Blue



PORTABILITY

- · Easy to remove battery pack
- Conveniently disassembles into four manageable pieces
- · Fits in most vehicle trunks

PERFORMANCE

- Top speed of 3.5 mph and enough power to get you where you want to go
- Twin motors for traction and precision handling

MANEUVERABILITY

· Compact design for a tight turning radius