

MODEL FP-mini

Powerful                 for the most demanding applications



**Technical data: FP-mini**

|                                      |                       |
|--------------------------------------|-----------------------|
| ➤ Machine length                     | 2,300 mm              |
| ➤ Infeed conveyor length             | 400 mm                |
| ➤ Cut off length                     | Max. 200 mm           |
| ➤ Forming depth                      | Max. 100 mm           |
| ➤ Top film width                     | 315 – 414 mm          |
| ➤ Bottom film width                  | 320 – 420 mm          |
| ➤ Top film thickness                 | 100 micron            |
| ➤ Bottom film thickness              | 200 – 300 micron      |
| ➤ Top and bottom film roll ext. dia. | Max. 300 mm           |
| ➤ Machine speed                      | 5 – 8 cycles / minute |
| ➤ Power                              | 380 V 50 Hz.          |
| ➤ Air supply                         | 6 – 10 bar            |
| ➤ Vacuum pump                        | 63 m3 Hr.             |
| ➤ Cooling water consumption          | 80 – 150 lt.Hr.       |

**General features:**

- > Designed for a variety of applications.
- > Stainless steel construction.
- > Small footprint.
- > Suitable for rigid and flexible films.
- > IP-65 protection class.
- > Vacuum and (MAP) packig systems.
- > Economic film consumption.
- > Sanitary design.
- > Easy access for tool change over.