



is gator tough

Gator Hose BTW-Series (2-Wire) final Crimp Specifications

Hose Type	Inches	Dash Size	Crimp Spec
PW - 1 Wire 4000 psi (Black)	3/8"	-6	0.816
PW - 2 Wire 6000 psi (Black)	3/8"	-6	0.817
PW - 1 Wire 4000 psi (Blue)	3/8"	-6	0.816
PW - 2 Wire 6000 psi (Blue)	3/8"	-6	0.817
SAE 100 R1AT / 1SN (1 Wire / Braid)			
	1/4"	-4	0.635
	3/8"	-6	0.804
	1/2"	-8	0.951
	5/8"	-10	1.05
	3/4"	-12	1.20
	1"	-16	1.566
	1 1/4"	-20	1.902
	1 1/2"	-24	2.15
	2"	-32	2.726
SAE 100 R2AT / 2SN (2 Wire / Braid)			
	1/4"	-4	0.675
	3/8"	-6	0.860
	1/2"	-8	0.992
	5/8"	-10	1.087
	3/4"	-12	1.290
	1"	-16	1.700
	1 1/4"	-20	2.03
	1 1/2"	-24	2.286
	2"	-32	2.85
SAE 100 R16 (2 Wire / Braid)			
	1/4"	-4	0.637
	3/8"	-6	0.811
	1/2"	-8	0.954
	5/8"	-10	1.154
	3/4"	-12	1.282
	1"	-16	1.601
SUPER FLEX 3,000			
	2"	-32	2.795



is gator tough

Gator Hose BTW-Series (4-Wire) final Crimp Specifications

Hose Type	Inches	Dash Size	Crimp Spec	
SUPER FLEX 3,000	2"	-32	2.852	API fitting
	2"	-32	2.795	4w fitting
R12 (4 wire)	3/4"	-12	1.382	
	5/8"	-10		
	1"	-16	1.630	
	1-1/4"	-20	2.045	
	1-1/2"	-24	2.220	
	2"	-32	2.880	4w fitting
	2"	-32	2.900	API fitting
4SH (4 wire)	3/4"	-12	1.395	
	5/8"	-10		
	1"	-16	1.645	
	1-1/4"	-20	2.000	
	1-1/2"	-24	2.220	