

# **2024**

# **BUMPER SWAP COMPACT**

## GENERAL RULES:

1. Must be registered before inspection.
  2. Anything deemed excessive will be at official's discretion.
  3. If the rules do not say you can do it, don't.
- 
1. **Front wheel drive 4/6 cylinder only.**
  2. **Cars must remain stock unless otherwise specified.**
  3. **Simplified harness allowed.**
  4. **No aftermarket oil coolers or tranny coolers.**
    - a. Factory tranny lines may be looped.
  5. **Factory or looped water systems only.**
    - a. No water boxes.
    - b. No rad guards
    - c. No expanded metal.
  6. **All doors may be wired or chained 8 spots per door max.**
    - a. 1-inch holed washer method permitted.
    - b. Drivers' door may be welded solid.
  7. **Deck lids may be wired or chained in 8 spots max.**
    - a. 1-inch holed washer method permitted.
    - b. Wiring can go to floor in spare tire area but cannot wrap around frame.
  8. **Hood may be wired in 6 spots max.**
    - a. You may use 1-inch holed washer method.
    - b. Must have a 12x12 fire hole.
    - c. Must be open for inspection.
  9. **Creasing of rear quarter panels permitted but must remain factory height.**
    - a. May tuck and dish trunk.

- 10. Frames may be hardnosed, but the core support may not be moved/removed.**
- a. No extra body mounts.
  - b. No fix it plates on fresh cars.
  - c. No seam welding
  - d. Pre ran cars with damage must get approval first for fix it plates.
- 11. Any factory car bumper may be used.**
- a. Bumpers may be seam welded but not loaded.
  - b. 4x4x1/4 tubing may be used.
    - i. If using this, you must keep ends open.
    - ii. No loading and no homemade point.
  - c. SMW LIGHT or MARK DOWD permitted.
    - i. 1/4 inch or less
    - ii. No gussets
    - iii. Ends must be open.
- 12. You may have a 6"x8" plate flat to front of frame for mounting purposes.**
- a. (1) 4"x 4" 1/4" plate per rail may be used to help attach bumper.
  - b. Must be welded to bumper and to the unibody only.
  - c. 2 strands of wire in 2 locations may go from core support to bumper.
- 13. Windshield must have wire or strapping.**
- 14. Rear window bars are not permitted.**
- 15. Battery may be moved to inside of car but does not have to be.**
- a. Must be securely fastened.
- 16. If gas tank is moved from under the car you must use a fuel cell, not a factory gas tank.**
- 17. Any air filled front tires.**
- a. May be doubled/tubed.
  - b. no bead locks or Lip protectors are permitted.
  - c. Rear tires may be solid.

**18. 4-point cages recommended**

- a. May have center bar for shifter only.
- b. Door bars may not exceed 6 inches past B-pillar.
- c. All cage material must remain 6 inches from the floor.
- d. No kickers/down legs.
- e. Halo bars permitted and must be straight up and down.
  - i. May connect windshield bar to halo.

**19. Tank protectors permitted.**

- a. May be no larger than 32 inches wide x 24 inches long x 24 inches tall.
- b. Must remain 4 inches from package tray and must be mounted to back bar.
  - i. **This will be strictly enforced.**

**20. Aftermarket shifters are permitted.**

**21. Headers are permitted.**

**22. Spring risers are permitted.**

- a. No solid suspension.
- b. All suspension components must remain stock.

**23. NO extra plates, NO extra wire.**