



STYLE
8000

Cradle to Cradle
Certified™ Bronze



WEAVING
EXCELLENCE
WITH
INNOVATION

Code	Color	SOLAR OPTICAL PROPERTIES				SHGC/G VALUE g-tot (glass & blind)	
		TS	RS	AS	TV	SINGLE 1/4 CL	INSULATING 1 HA
STYLE 8000 - 3%							
S01	Snow	38	54	8	36	0.40	0.27
S02	Eggshell	37	52	11	35	0.41	0.27
S03	Ecru	30	49	21	25	0.42	0.28
S04	Silver	30	46	24	22	0.44	0.29
S05	Smoke	23	38	39	9	0.46	0.30
S06	Seal	21	33	46	8	0.49	0.31
S07	Kohl	18	26	56	7	0.51	0.33



PRODUCT CERTIFIED FOR
LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818



MIF Seal of Approval



TS = Solar Transmittance
RS = Solar Reflectance
AS = Solar Absorptance
TV = Visual Transmittance

SHGC = Solar Heat Gain Coefficient

1/4 CL = 1/4" Clear Glass
1 HA = 1" Heat Absorbing Glass

Fabrics Installed Internally
Zero-Degree Profile Angle

For additional performance values, test references and technical definitions visit us at www.phifer.com.

S01 Snow




S02 Eggshell



S03 Ecu



S04 Silver



S05 Smoke



S06 Seal



S07 Kohl



Benefits of Style 8000 include:

- Cradle to Cradle Certified™ Bronze
- 100% Recyclable
- PVC free
- Halogen free
- Phthalate free
- Antimony Trioxide free
- Improved energy efficiency in dark colors
- LEED Material Ingredient Disclosure Credit Eligible

Colors may vary slightly from swatch sample. All variations are within industry standards.

STYLE 8000 SPECIFICATIONS

Cradle to Cradle Certified™ Bronze and constructed from 100% polyester yarn, Style 8000 is strong, light weight, and 100% recyclable. The unique 2x2 basketweave provides excellent fabric stability and enhances outward views.

FIRE CLASSIFICATION	California U.S. Title 19 (small scale)	BS 5867 Part 2 Type B Performance
	NFPA 101 (Class A Rating)	CAN/ULC-S 109 (large and small scale)
	NFPA 701 TM#1 (small scale)	CAN/CGSB2-4.162-M80
	NFPA 701 TM#2 (large scale)	IBC Section 803.1.1 (Class A Rating)

Fire classifications are subject to change. Please go to phifer.com for the most current information.

BACTERIA AND FUNGAL RESISTANCE	ASTM E 2180	ASTM G21
---------------------------------------	-------------	----------

ENVIRONMENTAL CERTIFICATION	Cradle to Cradle Certified™ Bronze
	GREENGUARD GREENGUARD Gold

Certified to these standards for low chemical emissions into indoor air during product usage

SAFE USE	RoHS/Directive 2002/95/EC	REACH (EC 1907/2006) compliant
	ANSI/WCMA A 100.1-2007 for lead content	
	US Consumer Product Safety Commission Section 101	

WARRANTY 5-year interior

ACOUSTICAL PERFORMANCE NRC (Noise Reduction Coefficient) and SAA (Sound Absorption Average) tested in accordance with ASTM C423-09a

UV PROTECTION Seal of Approval by the Melanoma International Foundation (MIF) for effectiveness in preventing sun damage to the skin or eyes

CLEANING INSTRUCTIONS Regular light dusting is suggested. Avoid rigorous vacuuming. Test an inconspicuous area before applying any cleaners.

RECOMMENDED CUTTING METHODS This fabric should be cut using ultrasonic or other heat generated methods. Railroading this fabric is not recommended.

STYLE 8000

WIDTHS	118" 300 cm
ROLL LENGTH	30 Linear Yards 27.4 Linear Meters
COMPOSITION	100% Polyester
MESH WEIGHT	7.35 oz/yd ² 249 g/m ²
FABRIC THICKNESS	0.019 in 0.47 mm
OPENNESS FACTOR	Approximately 3%
UV BLOCKAGE	Approximately 97%
ACOUSTICAL VALUE	NRC .20 / SAA .22

PHIFER
INCORPORATED

P. O. Box 1700 • Tuscaloosa, Alabama 35403-1700 USA
Phone: 205.345.2120 • FAX: 205.391.0799
Toll Free USA/Canada: 1.800.221.5497
www.phifer.com • ISO Registered



© SheerWeave is a registered trademark of PHIFER INCORPORATED.
™ Cradle to Cradle Certified is a mark licensed by the Cradle to Cradle Products Innovation Institute
™ UL, the UL logos and the UL mark are trademarks of UL LLC.
Photo courtesy of M+N Textiles, The Netherlands.
© PHIFER INCORPORATED V22 112822 3035030