

6" Channel Equipment Tilt (T6)

Lengths Available: 16' - 24'
 Deck Height: 21"
 Deck Width: 82"
 GVWR: 14,000 lbs (2 - 7k axles)
 15,680 lbs (Gooseneck)
 Load Angle: 11°

TREATED PINE DECK	DEXTER AXLE DEXTER EZ-LUBE AXLES	BULLDOG COUPLER	POWDER COAT	235/80/R16 RADIAL TIRES	KNIFE-EDGE TAIL
82" WIDE DECK	STEEL DIAMOND PLATE FENDERS	6" CHANNEL FRAME	14k BASE GVWR	3" CHANNEL CROSSMEMBERS	3M REFLECTIVE TAPE
LED LIFETIME LED LIGHTS	21" DECK HEIGHT	11° LOAD ANGLE	16" CROSSMEMBER CENTERS	TORSION SUSPENSION	7-WAY RV PLUG



Hydraulic Proportioning Valve



Hydraulic Cushioned Gravity Tilt

Our gravity tilts use a hydraulic cylinder, reservoir, and proportioning valve to control the rate the trailer tilts.



Knife-Edge Tail

Our 30" diamond plate knife-edge tail makes it super easy to load low clearance equipment like scissor lifts and fork lifts.



Low Load Angles

The use of torsion axles and our unique frame design allow us to keep our deck heights low, giving us extremely low load angles.