

SELF SEAL .080

PolyFoam Underlayment

WITH DOUBLE FILM LAMINATION



ADVANTAGES

- Polyethylene Foam with moisture resistant film on both sides
- Economical
- Humidity, Mold and Mildew resistant
- Special moisture resistant film Lip and self sealing tape for ease of installation
- Made with recycled materials.

PRODUCT SPECIFICATIONS

Thickness:

.080 (before film lamination) (+/-10%)

Foam Density:

1.7# Density (+/-15%)

Film Thickness: 2.5 mil HD/LD film out & 1 mil film in
(includes self sealing tape and adhesive)

WVTR (Water Vapor Transmission rate):

6.66 g/m²/24 hour day, (.43 g/100 in²/ 24 hour day)

Standard roll sizes:

48" x 25' (100 s.f.)

Standard Packing:

40 rolls per box, 52 boxes per truck, 2,080 rolls per truck

Stock Colors:

White & clear film



INSTALLATION INSTRUCTIONS

- Always read the flooring manufacturers recommendations and instructions before installing the underlayment.
- Before rolling out the underlayment, be sure to sweep, vacuum, and remove all debris on the substructure.
- Fill in any significant holes, gaps or breaks that may exist on the substructure.
- Roll out the Underlayment over the substructure with either side of the roll down.
- To connect the rolls together using the Self Sealing tape, simply join the extended film lip to the other end of the next roll by peeling off the liner of the adhesive tape and adhering it to the extended film lip.



Medallion
DIVISION OF STURLA INC.