



13 Executive Drive, Suite 19  
 Fairview Heights, Illinois 62208  
 Telephone: (618) 624-8783  
 Toll Free: (800) 272-7633  
 Fax: (618) 624-8777

**MATERIAL SAFETY DATA SHEET**

MAY BE USED TO COMPLY WITH OSHA'S HAZARD COMMUNICATION STANDARD, 29 CFR 1910.1200 AND SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (SARA) OF 1986 PUBLIC LAW 99-499. STANDARD SHOULD BE CONSULTED FOR SPECIFIC REQUIREMENTS

**SECTION I – IDENTIFICATION**

**MANUFACTURER'S NAME:** AMERICAN WELDING SYSTEMS INC.

**ADDRESS:** 13 EXECUTIVE DRIVE, SUITE 19

FAIRVIEW HEIGHTS, IL 62208

**IN CASE OF EMERGENCY:** 1(800) 272-7633

**PRODUCT NAME:** Quadcarb 6062 FCO

**PRODUCT CLASSIFICATION:** Composite Metal Cored Hardface Electrode for Open and Gas-Shielded Arc Welding

**SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION**

IMPORTANT: This section covers the material from which these products are manufactured. The fumes and gases produced when welding with normal use of these products are covered in Section V.

INGREDIENTS	CAS NO.	EXPOSURE LIMIT (mg/m <sup>3</sup> )		(By Weight)
		OSHA PEL	ACGIH TLV	PERCENT INGREDIENTS
Manganese <sup>1</sup>	7439-96-5	5 (fume)	0.2	15-21
Silicon	7440-21-3	5 (respirable) 15( dust)	10	0-1
Titanium	7440-32-6	15	10	2-6
Fluorides	7789-75-5	2.5	2.5	0-6
Iron	1309-37-1	10 (oxide fumes)	5 (oxide fumes)	Balance
Vanadium <sup>1</sup>	1314-62-1	0.1 (V <sub>2</sub> O <sub>5</sub> fume) 0.5 (dust)	0.05(V <sub>2</sub> O <sub>5</sub> fume)	0-3
Chromium <sup>1</sup>	7440-47-3	0.5	0.01 (Cr VI) 0.5 (metal)	10-15
Molybdenum	7439-98-7	5 (soluble)	0.5 (soluble/respirable) 3 (insoluble/respirable)	0-5
Nickel <sup>1</sup>	7440-02-0	1	0.1 (soluble) 0.2 (insoluble)	0-1
Zirconium	7440-67-7	5	5	0-2
Graphite	7782-42-5	5 (respirable)	2 (respirable)	1-7
Columbium	7440-03-1	-	-	0-6
Aluminum	7429-90-5	5 (respirable) 15 (dust)	5 (fume) 10 (dust)	0-2

<sup>1</sup> Subject to reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 (SARA) and 40 CFR Part 372

**SECTION III - PHYSICAL DATA**

Tubular wire containing alloys and minerals



13 Executive Drive, Suite 19  
Fairview Heights, Illinois 62208  
Telephone: (618) 624-8783  
Toll Free: (800) 272-7633  
Fax: (618) 624-8777

#### **SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

Non-Flammable: Welding arc and sparks can ignite combustibles and flammables. Refer to American National Standard Z49.1 for fire prevention during the use of welding and allied procedures.

Rating under National Fire Protection 704: Health, Hazard 0; Fire Hazard, 10; Reactivity Hazard, 0.

#### **SECTION V - REACTIVITY DATA**

Hazardous Decomposition Products: Welding fumes cannot be classified simply. The composition and quantity of both are dependent upon the metal being welded, the process, procedure, and the electrodes used. Other conditions which also influence the composition and quantity of the fumes and gases to which workers may be exposed include: coatings on the metal being welded (such as paint, plating, or galvanizing), the number of welders and the volume of the work area, the quality and the amount of ventilation, position of the welder's head with respect to the fume plume, as well as the presence of contaminants in the atmosphere (such as chlorinated hydrocarbon vapors from cleaning and degreasing activities).

When the electrode is consumed, fume and gas decomposition products generated are different in percent and form from the ingredients listed in Section II. Fumes and gas decomposition products, not the ingredients in the electrode, are important. The concentration of a given fume or gas component may decrease or increase by many times the original concentration in the electrode. Also, new compounds not in the electrodes may form. Decomposition products of normal operation include those originating from the volatilization, reaction, or oxidation of the materials shown in Section II, plus those from the base metal and coatings, etc., as noted above.

Reasonably expected decomposition products from normal use of these products include a complex of the oxides of the materials listed in Section II, as well as carbon monoxide, carbon dioxide, ozone and nitrogen oxides. The fume limit for chromium, nickel, manganese, and cobalt may be reached before the general limit for welding fumes (5mg/m<sup>3</sup>) is reached.

One recommended way to determine the composition and quantity of fumes and gases to which workers are exposed is to take an air sample inside the welder's helmet if worn or in the worker's breathing zone. See ANSI/AWS F12.1 "Method for Sampling Airborne Particles Generated by Welding and Allied Processes" and "Characterization of Arc Welding Fume" available from the American Welding Society, 550 N. W. LeJeune Road, Miami, FL 33126

#### **SECTION VI - HEALTH HAZARD DATA**

Electric arc welding or oxy fuel welding may create one or more of the following health hazards:

- Arc Rays can injure eyes and burn skin.
- Heat Rays (infrared radiation) from flame or hot metal can injure eyes.
- Electrical Shock can kill.
- Noise can damage hearing.

Carcinogenicity Chromium, nickel, cobalt, and their compounds are on the IARC and the NTP lists as posing a carcinogenic risk to humans.

Emergency and First Aid Procedures- Call for medical aid. Employ first aid techniques recommended by the American Red Cross.

Shielding Gases such as argon, helium, and carbon dioxide are asphyxiants and adequate ventilation must be provided.

Fumes and Gases can be dangerous to your health. Common Entry is by inhalation.

**Short term (acute)- overexposure to welding fumes may result in discomfort such as dizziness, nausea, or dryness or irritation of nose, throat, or eyes.**

Chromates present in the fume can cause irritation of the respiratory system, damage to lungs and asthma like symptoms.

Nickel compounds in the fume can cause a metallic taste, nausea, tightness in the chest, fever, and allergic reactions.

Manganese fume may cause flu like symptoms (metal fume fever).

Fluorides can cause pulmonary edema bronchitis.



13 Executive Drive, Suite 19  
Fairview Heights, Illinois 62208  
Telephone: (618) 624-8783  
Toll Free: (800) 272-7633  
Fax: (618) 624-8777

**Long Term (Chronic)- overexposure to welding fumes can lead to siderosis (iron deposits in the lung) and affect pulmonary function. Long term overexposure to manganese compounds may affect the central nervous system. Symptoms include muscular weakness and tremors similar to Parkinson's disease. Behavioral changes and changes in handwriting may also appear.**

Chromium VI compounds are required by OSHA to be considered carcinogenic. Long term exposure to Chromium and Chromium III Oxide dust can cause scaling, redness, itchiness, and a burning sensation on the skin.

Long term overexposure to nickel compound may cause lung fibrosis or pneumoconiosis. Soreness and itchiness of the nose and change in skin color and/or appearance may also result. Nickel and its compounds are required to be considered as carcinogenic by OSHA

This product contains or produces a chemical known to the State of California to cause cancer and birth defects (or other reproductive harm). (California Health and Safety Code § 25249.5 et.seq.)

Threshold Limit Value- The ACGIH 1994-95 recommended limit for welding fumes not otherwise classified (NOC) is 5 mg/m<sup>3</sup>. TLV-TWA's should be used as a guide in the control of health hazards and not as fine lines between safe and dangerous concentrations. See Section 5 for specific fume constituents which may modify this TLV-TWA.

#### **SECTION VII - PRECAUTION FOR SAFE HANDLING AND USE/APPLICABLE CONTROL MEASURES**

Read and understand the manufacturer's instructions and precautionary label on the product. See American National Standard Z49.1, Safety in Welding, Cutting, and Allied Processes, published by the American Welding Society, 550 N.W. LeJeune Road, Miami, FL 33126 and OSHA Publication 2206 (29CFR1910), U.S. Government Printing Office, Washington, D.C. 20402 for more detail on many of the following:

**Ventilation:** Use enough ventilation, local exhaust at the arc, or both, to keep the fumes and gases below the TLV's in the workers breathing zone and the general area. Train the welder to keep his head out of the fumes.

**Respiratory Protection:** Use respirable fume respirator or air-supplied respirator when welding in a confined space or where local exhaust or ventilation does not keep exposure below TLV.

**Eye Protection:** Wear a helmet or use a face shield with a filter lens. As a rule of thumb, start with a shade that are too dark to see the weld zone. Then go to the next lighter shade which gives sufficient view of the weld zone. Provide protective screens and flash goggles, if necessary, to shield others.

**Protective Clothing:** Wear head, hand, and body protection which help to prevent injury from radiation, sparks, and electrical shock. See ANSI Z49.1, at a minimum this includes welders' gloves and a protective face shield, and may include arm protectors, aprons, hats, shoulder protection, as well as dark substantial clothing. Train the welder not to touch live electrical parts and to insulate himself from work and ground.

**Procedure for Cleanup of Spills or Leaks-** Not applicable.

**Waste Disposal Method:** Prevent waste from contaminating surrounding environment. Discard any product, residue, disposal container, or liner in an environmentally acceptable manner, in full compliance with federal, state and local regulations.

The information in this MSDS was obtained from sources we believe are reliable. However, this information is provided without any representation or warranty, expressed or implied, regarding accuracy or correctness. The conditions or methods of handling, storage, use, and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons we do not assume responsibility and expressly disclaim liability of loss, damage, or expense arising from it or any way connected with the handling, storage, use, or disposal of the product.