

CLAUSB USB TO RS485 CONVERTER



- Designed to make serial port expansion quick and simple
- External 4-pin DIP switch to set RS-232, RS-422 or RS-485 mode conveniently
- DIN-rail mountable bracket for industrial environment
- Both a 6-pin terminal block and a DB9 male connector are available for optimal flexibility for serial connection
- Provides instant connectivity to RS-232, RS-422 and RS-485 communication devices serial port by connecting to a PC's USB port by connecting to its USB port
- Speed up to 38.4 kbps
- Powered by USB port - No external power supply required
- Includes: USB cable & driver
- Supports SmartLock®, Hurricane and Maestro controllers
- Ports: 1 RS232/422/485 port
- Speed: up to 38.4 kbps
- RS232 signals: TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
- RS422/485 signals: RS422 TxD+/-, RxD+/-, RTS+/-, CTS+/-, GND, RS485 Data+/-, GND
- Driver: Windows 98, ME, 2000, XP, 2003 Server, Vista and Windows 7
- Connectors: 1 DB9 male and terminal block
- Dimensions: 57 x 72 x 22 mm (W×L×H) 82 x 77 x 22 mm with DB9 connector and ears

C

MFG #	DESCRIPTION	EZ #
CA CLAUSB	USB Serial Communication Device	087108

ZODIAC® LINK FINGERPRINT READER KIT



- Enroll and manage up to 2,000 users (2 templates per user) right at the reader
- Use with a ZDCM door control module for a totally stand-alone solution
- Alternatively, allows existing proximity readers in a standard access control system to be upgraded to biometrics in under 5 minutes
- User templates can be copied from one unit to another - no need to re-enroll users should a unit need to be replaced
- Programmable via reader keypad
- Two line LCD display guides users easily through all programming functions
- No PC or software required
- No credentials required
- Includes: 1 Zodiac Link reader, 1 door control module, 1 enclosure, 1 power supply and 1 plug-in transformer

MFG #	DESCRIPTION	EZ #
CA ZODIACLINKKIT	Biometric Access Control Kit	082969

STANDALONE BIOMETRIC FINGERPRINT CYLINDRICAL LOCK



- Fake fingerprint/live finger detection
- Distinguishes between live and fake fingerprint by using electrostatic capacity technology
- Optical characteristics - analyses the image data achieved from certain angle lighting to the fingerprint using infrared
- Algorithm - detecting position differences between live and fake fingerprints using algorithmic analysis
- Fingerprint or prox bypass
- Enrolment/management via keypad
- Fingerprint user capacity of 100
- Bypass proximity capacity of 50 cards
- Verification time (1:1) < 1 sec
- Identification (1:N) time (100 templates) < 2 sec
- Low battery audible warning
- Requires 4 x 1.5 V AA Alkaline batteries, 6 V (not included)
- Battery life: approx 1 year/7,200 cycles
- Operating temperature: -20°C to +50°C
- Humidity: < 90% RH, non-condensing
- 161 standard door prep
- Latch: 2-3/4" backset, 1/2" throw
- Door thickness: 1-3/8" and 1-3/4"

MFG #	DESCRIPTION	EZ #
UC DL473FR	Biometric Cylindrical Lock	105795

5600 SERIES ELECTRIC STRIKE



- Intended for use with Adams Rite style deadlatches or cylindrical latches
- For use on hollow metal or aluminum jambs
- Designed for use with access control systems for electronically locking and unlocking
- Faceplate: standard 4-7/8" x 1-11/16" x 1-5/8" clear aluminum - comes with 2; 1 square & 1 radius corner
- Current draw: 230mA @ 12V, 130mA @ 24V
- Voltage: 12VDC and 24VAC
- Fail safe or fail secure - field reversible

MFG #	DESCRIPTION	EZ #
CA TA5600 12DC	Electric Strike	105789

DOOR CONTACT



- Recessed 3/4" door contact
- UL listed contact designed to provide a clean and easy installation for standard openings
- Provides a wide 1-1/4" opening gap
- Max. carry current: 1.0 amp
- Max. switching current: 0.3 amp
- Operating temperature range: 0°C to +49°C

MFG #	DESCRIPTION	EZ #
CA CONTACTCL	Contact	105796