

下蓋-印刷字稿

Lithium Iron Phosphate Battery PAB-700-12V5Ah



• Nominal voltage : 12 V
• Full charge capacity : 5 Ah (at 22°C)
• Continuous current discharge ration : 5 A
• Continuous current charge ration : 2 A
• Operating temperature range : -20°C to 65°C
• Storage temperature range : -30°C to 65°C
• Full Capacity Rating [Ah] @ 1C rate : 5 Ah
• Full Capacity Rating [Wh] @ 1C rate : 60 Wh
• Max Discharge Current : 50A/0.5sec
• Short Circuit Protection Type and Ratings : Mosfet/0.7sec
• Passed UL1973 certification
• Passed International Protection IP67
• Manufacturer : Prefco Green Power Inc.
• Manufacturing location : Made in Taiwan

CAUTION :
Lithium iron rechargeable batteries inside.
Do not damage or mishandle this package.
If package is damaged, batteries must be
quarantined, inspected, and repacked.
For chemical emergency Spill Leak Fire Exposure
or Accident, Contact Emergency Services.

MISE EN GARDE :
Piles rechargeables au fer de lithium à l' intérieur.
Ne pas endommager ni manipuler cet emballage.
Si l'emballage est endommagé, les batteries
doivent être mises en quarantaine, inspectées et
réemballées.
En cas d'urgence chimique, d'exposition ou
d'accident lié à une fuite de déversement,
contactez les services d'urgence.

WARNING : Risk of Fire, Explosion, and Burns. Do not
Disassemble, Crush, Heat Above 100°C (212°F), or Incinerate.



下蓋-印刷字

Lithium Iron Phosphate Battery PAB-700-12V5Ah



• Nominal voltage : 12 V
• Full charge capacity : 5 Ah (at 22°C)
• Continuous current discharge ration : 5 A
• Continuous current charge ration : 2 A
• Operating temperature range : -20°C to 65°C
• Storage temperature range : -30°C to 65°C
• Full Capacity Rating [Ah] @ 1C rate : 5 Ah
• Full Capacity Rating [Wh] @ 1C rate : 60 Wh
• Max Discharge Current : 50A/0.5sec
• Short Circuit Protection Type and Ratings : Mosfet/0.7sec
• Passed UL1973 certification
• Passed International Protection IP67
• Manufacturer : Prefco Green Power Inc.
• Manufacturing location : Made in Taiwan

CAUTION :
Lithium iron rechargeable batteries inside.
Do not damage or mishandle this package.
If package is damaged, batteries must be
quarantined, inspected, and repacked.
For chemical emergency Spill Leak Fire Exposure
or Accident, Contact Emergency Services.

MISE EN GARDE :
Piles rechargeables au fer de lithium à l' intérieur.
Ne pas endommager ni manipuler cet emballage.
Si l'emballage est endommagé, les batteries
doivent être mises en quarantaine, inspectées et
réemballées.
En cas d'urgence chimique, d'exposition ou
d'accident lié à une fuite de déversement,
contactez les services d'urgence.

WARNING : Risk of Fire, Explosion, and Burns. Do not
Disassemble, Crush, Heat Above 100°C (212°F), or Incinerate.

