

PRELIMINARY SPECIFICATIONS



RGS PRO SYSTEMS
408 South Main Street, Suite # 1
Zelienoplle, PA 16063
Phone (724) 452-8701
Fax (724) 452-8709
www.rgsprosystems.com
email: sales@rgsprosystems.com

"Redefining Great Sound"



115XS-ASY

System Type	Vented 15" 2-Way Trapezoid Enclosure
Passive/Active	Passive / Biamp Available
Frequency Response	50 Hz - 20 KHz +/- 3 dB
Crossover Frequency (Hz)	1000 Hz
HF Driver	1.4" Compression Driver
LF Driver	(1) 15" Woofer
System Dispersion	50° Horizontal (Top) x 100° (Bottom)
(Asymmetrical Horn)	55° Vertical (Nominal)
Power (Watts)	1000 Watts RMS/2000 Watts Program
Nominal Impedance	8 Ohms
Sensitivity (dB @ 1W/1M)	101 dB
Max SPL (dB)	135 dB @ 1 Meter
Enclosure Materials:	1/2" or 3/4" Multi-Ply Birch
Inputs	2 Parallel Speakon
Flying Hardware	Optional
Dimensions:	32 3/4" H x 17 " W x 19 1/4" D, Back W 10 3/4"
Weight	75 Lbs
Finish	DuroBlast (Polyurea)
Color	Black, White, Custom, Stained